

PRIMARY CORNER DESCRIPTION SE Cor. Section 5

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6891)

-----  
Set post cor. secs. 4, 5, 8 and 9, from which  
A Fir 6" dia., bears N.15°E., 18 lks. dist.  
A Fir 4" dia., bears N.70°W., 22 lks. dist.  
A Fir 5" dia., bears S.5°W., 14 lks. dist.  
A Fir 40" dia., bears S.40°E., 18 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6965)

-----  
The cor. to secs. 4, 5, 8 and 9, which is a Fir tree 6" dia., and not a post, as given in the field notes furnished, mkd. T30S S4 on NE.; R3W S9 on SE.; S8 on SW.; and S5 on NW. faces with 4 notches on E. and 5 notches on S. edges, from which  
A Fir 6" dia., bears N.15°E., 18 lks. mkd. T30S R3W S4 BT.  
A Fir 40" dia., bears S.40°E., 18 lks. mkd. T30S R3W S9 BT  
A Fir 5" dia., (18" now) bears S.5°W., 14 lks. dist. mkd. T30S R3W S8 BT.  
A Fir 4" dia., (8" now) bears N.70°W., 22 lks. dist. mkd. T30S R3W S5 BT.

I destroy the marks on the SE. and SW. faces, of this cor. and the marks on the witness trees in secs. 8 and 9. The witness tree in sec. 4 is dead. In it's stead,  
I marked a Fir 11" dia., which bears N.36½°E., 27 lks. dist. mkd. T30S R3W S4 BT.

George Wenderoth - 4/1952 (Filed Feb. 1, 1963) - C.S. 52/138-53

-----  
Found - 20" Fir N.36°30'E., 17.8 ft., dead.  
16" Fir N.72°W., 14.5 ft., dead.  
Drive 1/2" I.Pipe for corner.  
Scribe - 32" Fir N.32°30'E., 75.6 ft., dead but sound.  
No other trees available.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Jan. 1963 - C.S. File 52/138-6

-----  
Found - Orig. 8" now 8" snag, shows good scribing, N.70°W., 14.5 ft.  
Orig. 40" now dead 40" Fir, S.40°E., 11.9 ft., shows scar.  
Find 1/2" I.Pipe at corner. No other BTs.

Set brass cap alongside cor. I.P. and mkd. "County Surveyors Office 1963 S 5 | T30S R3W  
S9

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION SE Cor. Section 5

Alias	Description

<p>New BTs- 6" Laurel bears S.8°W., 25.8 ft. scribed S9 CS BT. 5" R.Fir bears N.47°W., 26.8 ft. scribed S5 CS BT.</p>
<p>Fd. OK by D. Edwards, Dec. 1999 - M133-66</p>
<p>Douglas Co. Surveyor's Office - Crew: Stephen J Flause &amp; Jeffery Lorsung - 9/12/2018 - C.S. File 67/45-21 ----- Found - A 1" i.d. iron pipe by Byron, in 1963 set, projecting 17" above the ground with a 2½" brass cap (properly) mkd A 1/2" iron pipe by Wenderoth in 1952 is set along the SW edge of the BCIP Original BTs by Hathorn in 1857: A root hole bears N.15°E., 11.9 ft. A 36"x14' tall rotted D.Fir snag bears, S.45°E., 13.0 ft. with an opened upper and a healed lower blaze. (Rec S.40°E., 18 lks.) A BT by Bushey, USGLO Deputy Surveyor, in 1893: A rotted fir and root hole bears, N.36½°E., 17.8 ft. A BT by Byron in 1963: A 14"x4' tall madrone stump with a healed blaze bears S.6½°W., 25.8 ft. to a new 8" galv. spike set in the center of the stump. (Rec S.8°W.) New - A 14"x1.5' tall D.Fir stump bears N.77½°E. 4.8 ft to a 8" galv. spike set in the center of the stump. A 5/8"x30" iron rod projecting 8" above the ground with a yellow plastic cap marked "DOUG. CO SURVEYOR" bears West, 13.00 ft. A 5/8"x30" iron rod projecting 9" above the ground with a yellow plastic cap marked "DOUG. CO. SURVEYOR" bears North 15.00 ft. Found a 6' galv. U-Post bears West, 1.5 ft. LOCATION &amp; COMMENTS: All BTs have BT tags attached. All new BTs have double blazed faces with bearings measured to the center of the tree at the root crown and distances measured to the side and center of the root crown. The centerline of an unnamed dirt forest access road, course NE-SW, in a clearcut unit bears West, 55 ft. GEODETIC COORD. N 491,092.85 E4,231,124.65 LAT: 42°59'06.070"N LONG: 123°04'47.201"W DATUM: NAD 83, Epoch 2010.00 SOURCE: Trimble GeoXT 6000 COMPASS DECLINATION: 15°E.</p>