

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 300626

PRIMARY CORNER DESCRIPTION C C for Secs. 4 & 9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6951)

At point of intersection, Set a Dogwood post, 4 ft. long, 4" sq., 24" in the ground, for closing cor. to secs. 4 and 9 mkd. CC T30S R3W on E.; S4 on N.; and S9 on S. faces, with 5 notches on S. and 4 notches on E. faces, from which
A Fir 5" dia., bears N.13½°E., 29 lks. dist., mkd. T30S R3W S4 BT.
A Laurel 6" dia., bears S.17¼°E., 32 lks. dist. mkd. T30S R3W S9 BT.
A Fir 5" dia., bears S.37°W., 64 lks. dist., mkd. T30S R3W CC S4 and 9 BT.

George J. Wenderoth - April 1952 (filed Feb. 1, 1963) - C.S. File 52/138-53

Placed by measurements North and South.
Drive ½" I.Pipe for corner, from which I scribe
10" Fir N.33°E., 37.8 ft.
14" Maple S.31°35'E., 27.4 ft.

Tony Hostetter - For: Roseburg Resources - 6/2006 - M151-9

Found - ½" iron pipe as set by Wenderoth (CS File 52/138) from which;
18" fir, face evident now windfall (N.33°E. 37.8 ft)
19" fir, BLM tag (unknown BT) bears; S.41"E. 45.7 ft
New BTs- 26" fir, scribed S9 NW BT bears; S.74°07'E., 34.4 ft to spike.
6" cedar, scribed S9 NW BT bears; S.53°51'E., 13.2 ft to spike.
32" fir, scribed S9 NW BT bears; S.22°50'E, 59.0 ft. to spike.