

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 337100

PRIMARY CORNER DESCRIPTION C C for Secs. 4 & 5 only, T31-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 - (DCSO records, Vol. 18 Pg 7758-59  
-----

At point of intersection, Set a stone 12x10x10 ins., 8" in the ground, for closing cor. to secs. 4 and 5, marked C C on S. with 4 notches on E. and 2 notches on W. faces; from which  
A Fir 15" dia., bears S.12¼°E., 75 lks. dist. mkd. T31S R3W S4 BT.  
A Laurel 10" dia., bears S.32½°W., 21½ lks. dist. mkd. T31S R3W S5 BT.  
A Fir 9" dia., bears N.11½°W., 36 3/4 lks. dist. mkd. T31S R3W C C S4 and 5 BT.

Survey by John H. Markham, Jr. - For: Joe Ritter - Wit: Geo. Vaughn - Aug. 8, 1951 - C.S. File 40/363-2  
-----

Determined by old bearing trees:  
A Fir 15" dia., bears N.11°W., 24.4 ft., I chopped out and found the scribe.  
A 36" Fir, windfall, bears S.12°E., 50.0 ft.  
At corner point, found large stone and drove 1" x 30" Iron pipe, from which  
A Laurel 8" dia., bears S.23°W., 12.0 ft. mkd. S5 T31S R3W BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Jan. 1966 - C.S. File 52/63  
-----

Found - Iron pipe at sec. corner.  
8" Laurel now 13", S.23°W., 12.0 ft., bark scribed.  
15" D.Fir now 20", N.11°W., 24.4 ft., orig. BT, opened, parts of scribing visible.  
Set Brass cap alongside Iron pipe and marked:  
County Surveyors Office  
T30S R3W  
S 33  
-----  
S 5 | S 4  
T31S R3W  
1966  
New BTs- 19" D.Fir, North 31.8 ft. scribed T30S R3W S33 CS BT  
13" Laurel S.23°W. 12.0 ft scribed T31S R3W S5 CS BT

BLM resurvey by A. Bert Skeesick Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2000, 2100, & 2300, surveyed Nov. 2004/Feb. 2005 - (DCSO rec. Vol. 55 Page(s) 21501-4) & 2008-1 thru 2008-4 Plats  
-----

The CC of secs. 4 & 5, T31S R3W, on the S. bdy of the Tp, cont.

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 337100

PRIMARY CORNER DESCRIPTION C C for Secs. 4 & 5 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

perpetuated by Markham in 1951, further perpetuated by Powell in 1966, monumented with an iron pipe, 1½" dia., firmly set, projecting 18" above the ground, with no cap) with brass cap (properly) mkd.

from which the remains of the orig. BTs

A roothole bears S.32½°W., 14.2 ft. no trunk remains.

A decayed & burnt fir stump, 5" dia., bears N.11½°W., 24.3 ft. with no marks visible.

and the remains of a BT mkd by Powell

A sawed & burnt fir stump, 13" dia., bears North, 31.8 ft. with no marks visible.

and new accessories

A rebar, 30" long, 5/8" dia., driven 28" I the ground for a reference monument, bears S.5°E., 7.50 ft. with alum. cap mkd RM T31S R3W S4 7.5 FT TO COR 2005 and an arrow point to the cor.

A rebar, 30" long, 5/8" dia., driven 28" I the ground for a reference monument, bears S.85°W., 7.50 ft. with alum. cap mkd RM T31S R3W S4 7.5 FT TO COR 2005 and an arrow point to the cor.

Fd. & Used on BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2127 surveyed Feb/April 2006- (DCSO records Vol. 57 Page(s) 22508-9)