

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 340140

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 33

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM Dependent resurvey by Timothy J Moore, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2127 surveyed Feb/April 2006- (DCSO records Vol. 57 Pgs 22529-30)

-----  
Point for the center ¼ sec. cor. of sec. 33, at intersection with the E. and W. centerline.

Set a stainless steel post, 28" long, 2½" dia., 23" in the ground, with brass cap mkd.

T30S R3W  
C ¼  
S 33  
2006

from which

An iron rod, 30" long, 5/8" dia., driven 30" in the ground for a reference monument, bears S.30°00'00"E., 15.00 ft., with aluminum cap mkd. RM C ¼ S33 15.0 FT TO COR 2006 and an arrow pointing to the cor.

An iron rod, 30" long, 5/8" dia., 30" in the ground for a reference monument, bears S.60°00'00"W., 8.00 ft. with aluminum cap mkd. RM C ¼ S33 8.0 FT TO COR 2006 and an arrow pointing to the cor.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this point, the cor. of 4-strand barbed wire fences bears N.13¾°W., 27.0 ft., extends North and East.