

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6882)

Marked a Fir 36" dia., for ¼ sec. post, from which
A Fir 18" dia., bears N.65°W., 50 lks. dist.
A Fir 12" dia., bears S.80°E., 92 lks. dist.

Survey by John H. Markham, Jr. - Wit: Geo. Vaughn - ~~Oct. 4~~, 8/8/1951 - C.S. File ~~40/381~~ 40/363-4 *(corrected 8/6/2024)

Determined by old bearing trees:
A Fir 30" dia., bears N.61°W., 33.0 ft., found bark scribe
A Fir 36" dia., bears S.82°E., 62.0 ft.
At corner point, found rotten stump of O.B.T. set for corner point. I drove a 1" x 30" Iron pipe, from which
A Maple 6" dia., bears N.10°E., 17.5 ft. mkd. ¼S BT

Fd. OK, April 1986 by Wm. Ruppert - C.S. File 63/36
Fd. OK, June 1994 by M. Heimbürger - M 120-22

BLM resurvey by A. Bert Skeesick Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2000, 2100, & 2300, surveyed Nov. 2004/Feb. 2005 - (DCSO rec. Vol. 55 Page(s) 21501-4) & 2008-1 thru 2008-4 Plats

The ¼ sec. cor. of secs. 28 & 33, perpetuated by Markham in 1951 monumented with an iron pipe, 1" dia., 23" long, firmly set, projecting 9" above the ground (iron pipe is set in the center of a decayed stump hole, 40" dia., with outer ring of fir bark) from which the remains of the orig. BTs

A sawed & burnt fir stump, 52" dia., bears S.78°E., 64.5 ft. with no marks visible. (Rec. S.80°E., 60.7 ft.)

A sawed & burnt fir stump, 33" dia., bears N.57½°W., 33.0 ft. with no marks visible (Rec. N.65°W.)

and the remains of a BT mkd. by Markham

A maple stump, 7" dia., bears N.9°W., 17.5 ft. with no marks visible.

At the corner point

Set an iron post, 28" long, 2½" dia., 25" in the ground, directly over the iron pipe, with brass cap marked:

T30S R3W

¼ S 28
S 33

2004

from which

A fir, 4" dia., bears S.77°W., 11.9 ft. mkd. X BT.

A fir, 15" dia., bears N.1°W., 30.0 ft. mkd ¼ S28 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

cont.

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

FD. & used on BLM Dependent resurvey by Timothy J Moore, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2127 surveyed Feb/April 2006- (DCSO records Vol. 57 Page(s) 22516-7)

Fd. Ok by Neil Hibbs - 1/2026 - 2026-0010