

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 21

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6960)

-----  
Set a quartz stone 12 x 12 x 8 ins., 8" in the ground, for ¼ sec. cor. marked ¼ on N. face, from which

A Laurel 9" dia., bears S.18 3/4°E., 66 lks. dist. mkd. ¼ S BT.

A Fir 8" dia., bears N.16 3/4°W., 110 lks. dist. mkd. ¼ S BT.

BLM resurvey by Stephen D. Albright and Jack W. Bowder, Cadastral Surveyors, under Group #776, surveyed June/July 1972 - (DCSO records Vol. 36 Page(s) 14983)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 30 S R 3 W

1/4  $\frac{S\ 16}{S\ 21}$

1972

from which

A Fir 14" dia., bears N.33½°W., 88 lks. dist. mkd. ¼ S16 BT.

A Fir 13" dia., bears S.54°W., 93 lks. dist. mkd. ¼ S21 BT  
Corner is located on a spur sloping S.45°E.

Greg Lang - Oct. 2004 - C.S. File 65/52-14

-----  
Found - 3½" BLM Brass cap

24½" D.Fir bears N.33¾°W., 57.50'

25" D.Fir bears S.44½°W., 60.30'

22½" D.Fir bears N.69½°E., 77.80' scribed "¼ S16 BT"

13" D. Fir bears S.35½°E., 38.50' scribed "¼ S21 BT"

NOTE - We set & measured to spikes in the base of all BTs; bearings to the trees are based on BLM's 1972 survey line from the N¼ Corner to the NW Section Corner of Section 21 (S.89°41'00"W).

Corner lies on the top of a ridge & in a dirt road.

Fd. Ok by Greg Lang, 1/2007 - M152-13

James Klein & Richard Kitz - For: Pacific Connector Gas Pipeline Project/Williams - Sept. 2014 - M166-19 A-E; revised by M166-45 A-E

-----  
Found - 3¼" brass cap stamped BLM, date is illegible corner is in a gravel road. continued next page

