

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 9 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6964)

Set a Fir post 4 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S. on N. face, from which

A Fir 40" dia., bears N.42°W., 14¼ lks. dist. mkd. ¼ S BT

A Fir 12" dia., bears S.27½°W., 43 lks. dist. mkd. ¼ S BT

Douglas Co. Surveyors Office - John M. Powell, Cliff Stone, crew - Oct. 27, 1966 - C.S. File 54/52-8

Found - 40" D.Fir now stump, N.42°W., 9.3 ft., shows good scar.

12" D.Fir now stump, S.27½°W., 28.4 ft., opened for scribing.

Set Brass cap at cor. mkd: County Surveyors Office

T 30 S R 3 W

S 9

S 16

1966

New BTs- 6" Laurel S.83°E., 24.1 ft. mkd. ¼ S16 CS BT.

4" D.Fir N.60°E., 8.8 ft. mkd. ¼ S9 CS BT.

Fd. OK, June 1993 by G. Lang - M 123-14

Greg Lang - Nov. 2004 - C.S. File 65/52-16B

Found - DCSO Brass cap

18" D.Fir bears N.64½°E., 8.7' (1966 by DCSO)

9½" Madrone bears S.83½°E., 24.0' (1966 by DCSO)

40" Fir stump bears N.36°W., 9.6' (original)

12" Fir stump bears S.29°W., 27.7' (original)

New - 11" D.Fir bears N.21½°W., 10.7' scribed ¼ S9 BT"

11" D.Fir bears S.37°W., 17.1' scribed ¼ S16 BT"

Note - We set and measured to spikes in the base of all bearing trees; bearings to the trees are based on BLM's 1972 survey line from the N1/4 Corner to the NW Sec. Corner of Section 21 (S.89°41'00"W.).

Fd. Ok by Greg Lang, 1/2007 - M152-13