

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 376100

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. for Sec. 4 only, T31-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Howard Johnstone - For: Roseburg Lumber Co. - June 10, 1982 - M 92-44

Set 5/8" x 36" iron rod and alum. cap mkd. LS 498, from which
25" Fir bears N.8°W., 5.4 ft.
7" Fir bears S.64°W., 9.5 ft.

BLM Dependent resurvey by Timothy J Moore, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2127 surveyed Feb/April 2006- (DCSO records Vol 57 Page 22507)

(From the CC of Secs. 33 & 34 only on the S bdy of the Tp)
S.89°52'53"W., @ 149.01 ft:
A point established as the ¼ sec. cor. of sec. 4 only by Johnstone, in 1982, bears South, 0.43 ft., monumented with an iron rod, 5/8" dia., firmly set, projecting 4" above the ground, with aluminum cap mkd. T31S R3W SEC 4 ONLY ¼ LS 498 1982, from which the remains of a bearing tree mkd. by Johnstone

A roothole bears N.2½°W., 5.6 ft., with no trunk remains.

THIS POINT WAS ESTABLISHED USING IMPROPER PROCEDURES AND IS NOT ACCEPTED AS THE COR

@ 186.02 ft.
Point for the ¼ sec. cor. of sec. 4 only, not monumented.