

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 33 and 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol 16 Pages 6942-43)

-----  
Set an Alder post 4 ft. long, 4' sq., 24" in the ground, for ¼ sec. cor. marked ¼ S. on W. face, from which  
A Fir 8" dia., bears S.35°W., 19½ lks. dist. mkd. ¼ S BT  
An Alder 8" dia., bears S.9°E., 29½ lks. dist. mkd. ¼ S BT

Survey by Howard W. Johnstone, LS #498 - For: Roseburg Lumber Co. - Aug. 26, 1983 - M 95-6

-----  
Set 1" x 36" Iron pipe and brass cap mkd. LS 498, from which  
New BTs- 10" Fir S.63°E., 25.5 ft.  
19" Fir N.42°W., 24.0 ft.

BLM Dependent resurvey by Timothy J Moore, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2127 surveyed Feb/April 2006- (DCSO records Vol. 57 Page(s) 22513)

-----  
The ¼ sec. cor. of secs. 33 and 34, established by Johnstone, in 1983, and is accepted as the cor., monumented with an iron rod, 5/8" dia., firmly set, 3" below the surface of the ground, with aluminum cap (properly) mkd.  
from which the remains of a bearing tree mkd. by Johnstone  
A sawed and decayed fir stump, 14" dia., bears N.45½°W., 23.9 ft., with no marks visible.  
and new bearing trees  
A fir, 7" dia., bears N.84¾°E., 10.3 ft., mkd. ¼ S34 BT.  
A fir, 8" dia., bears N.21¼°W., 20.7 ft., mkd. ¼ S33 BT.

Fd. as per rec. by R Brown, 4/2016 - 2016-0016