

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6944)

Set a quartz stone, 12 x 12 x 6 ins., 8" in the ground, for 1/4 sec. cor. marked 1/4 on W. face, from which
A Fir 12" dia., bears N.42 1/4°E., 9 lks. dist. mkd. 1/4 S BT
A Fir 15" dia., bears S.17°W., 56 lks. dist. mkd. 1/4 S BT

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Jan. 1963 - C.S. File 52/138-15

Found - Rock at corner as recorded.
Orig. 12" now 19" R.Fir N.43°E., 5.9 ft., shows good scars.
Orig. 15" now 32" R.Fir S.17°W., 35.7 ft., shows good scars.

Set brass cap alongside cor. stone and marked:
County Surveyors Office
T 30 S R 3 W
1/4 S21 | S22
1963

No new bearing trees scribed.

Fd. and used in BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1294, Surveyed May/June 1986 - (DCSO records Vol. 48 Page(s) 18228)

James Klein & Richard Kitz - For: Pacific Connector Gas Pipeline Project/Williams - Sept. 2014 - M166-19 A-E; revised by M166-45 A-E

Found - 2 1/2" brass cap stamped County Surveyors Office 1963
BTs - 23.5" Fir with healed face (original BT) with tag dated 1986 N.42°E., 5.9'
48" Fir with healed face and tag dated 7/72; S.55°E., 17.5'
34" Fir with tag dated 1986 S.17°W., 37.0'