

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO recs Vol. 16 Pages 6944-45)

Set a Chinquapin post, 4 ft. long, 4" sq., 24" in the ground, for cor. to secs. 15, 16, 21 and 22, marked T30S S15 on NE.; R3W S22 on SE.; S21 on SW.; and S16 on NW. faces, with 3 notches on E. and S. edges, from which

- A Fir 16" dia., bears N.75°E., 33 lks. dist. mkd. T30S R3W S15 BT.
- A Fir 15" dia., bears S.6¼°E., 45 lks. dist., mkd. T30S R3W S22 BT.
- A Fir 33" dia., bears S.34 3/4°W., 42p lks. dist. mkd. T30S R3W S21 BT.
- A Fir 30" dia., bears N.70¼°W., 10 lks. dist. mkd. T30S R3W S16 BT.

BLM resurvey by Stephen D. Albright and Jack W. Bowder, Cadastral Surveyors, under Group #776, surveyed June/July 1972 - (DCSO records Vol. 36 Page(s) 14980-81)

The Sec. corner, determined at record bearing and distance from the remains of the original bearing trees:

- A root hole bears N.75°E., 33 lks. dist., with the decayed remains of a Fir alongside, size indeterminate, no marks visible.
- A decayed Fir stump, size indeterminate, bears S.6¼°E., 45 lks. dist., with axe marks visible on old blaze.
- A decayed Fir stump, size indeterminate, bears S.34°W., 42½ lks. dist., no marks visible.
- A root hole bears N.70¼°W., 10 lks. dist.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 18" in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd:

T 30 S R 3 W
S 16 | S 15
S 21 | S 22
1972

from which new bearing trees:

- A Fir 5" dia., bears N.55½°E., 26½ lks. dist. mkd. X BT.
- A Fir 5" dia., bears S.41°E., 14½ lks. dist. mkd. X BT.
- A Fir 6" dia., bears S.28°W., 23 lks. mkd. T30S R3W S21 BT
- A Fir 5" dia., bears N.36½°W., 48 lks. dist. mkd. X BT.

Fd. and used in BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1294, Surveyed May/June 1986 - (DCSO records Vol. 48 Page(s) 18228-29)

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Greg Lang - Aug. 2005 - C.S. File 65/54-31

Found - BLM brass cap & BTs per their 1972 survey.
10½" fir bears N.35½°W., 29.60' (BLM 1972 rec is N.36½°W., 31.68')
12" fir bears N.56°E 17.20' (BLM 1972 rec is N.55½°E 17.49')
12½" fir bears S.29½°W. 14.80' (BLM 1972 rec is S.28°W., 15.18')
12" fir bears S.40½°E., 9.30' (BLM 1972 rec is S.41°E 9.57')

Note - We set and measured to spikes in the base of all BTs; bearings to the trees are based on BLMs survey of the West line of Section 22.
Corner is located on the northwest side of a ridge about 550' south of the creek.

Fd. Ok by Greg Lang, 1/2007 - M152-13

BLM Corrective Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, under Group No. 2134, surveyed March/April 2006 - (DCSO records Vol. 56 Page(s) 22105-6)

The cor. of secs. 15, 16, 21, and 22, monumented with an iron post, 2½" dia., firmly set, projecting 12" above ground, with brass cap (properly) mkd.

from which the remains of an original bearing tree

A decayed fir stump, size indeterminate, bears S.34¾°W., 28.0 ft., with no marks visible. (Record, 31.0 ft.)

and bearing trees mkd. by Albright and Bowder

A fir, 12" dia., bears N.55½°E., 17.5 ft., with a healed blaze and steel spike, ¼" dia., driven into left side.

A fir, 11" dia., bears S.41°E., 9.6 ft., with a healed blaze and steel spike, ¼" dia., driven into left side.

A fir, 11" dia., bears S.28°W., 15.2 ft., with a healed blaze and steel spike, ¼" dia., driven into right side.

A fir, 12" dia., bears N.36½°W., 29.6 ft., with a healed blaze and steel spike, ¼" dia., driven into right side.

BLM visit, May 2008, Kenneth W. Saveland, no field notes or new corner report see retracement plat dated 2011

Latitude 42°57'38.02"N Longitude 123°03'40.71"W
(NAD 1983 (CORS 96))

continued next page

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

James Klein & Richard Kitz - For: Pacific Connector Gas Pipeline Project/Williams - Sept. 2014 - M166-19 A-E; revised by M166-45 A-E

Found - 3¼" brass cap stamped BLM, 1972
BTs - 13.8" Fir with healed face and BLM tag dated 7/72;
N.55½°E., 17.5' to nail side center
12" Fir with tag dated 08/05; S.40½°E., 9.3' to nail side center
13" Fir with healed face and BLM tag dated 08/72;
S.28°W., 15.2' to nail side center
12.3" Fir with healed face and BLM tag dated 07/72;
N.36½°W., 31.7' to nail side center