

PRIMARY CORNER DESCRIPTION ¼ Cor. for Secs. 15 and 16

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6946)</p> <p>-----</p> <p>Set a stone 12 x 10 x 6 ins., 8" in the ground, for ¼ sec. cor., marked ¼ on W. face, from which</p> <p> A Hemlock 8" dia., bears S.69½°E., 7½ lks. dist. mkd. ¼ S BT.</p> <p> A Cedar 8" dia., bears N.39½°W., 34 lks. dist. mkd. ¼ S BT</p>
<p>BLM resurvey by Stephen D. Albright and Jack W. Bowder, Cadastral Surveyors, under Group #776, surveyed June/July 1972 - (DCSO records Vol. 36 Page(s) 14981-82)</p> <p>-----</p> <p>The ¼ sec. cor., determined at record bearing and distance from the remaining original bearing tree:</p> <p> A Cedar 18" dia., bears N.39½°W., 34 lks. dist., with scribe marks S BT visible on opened blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:</p> <p style="text-align: center;">T 30 S R 3 W ¼ S16 S15 1972</p> <p>from which new bearing trees</p> <p> A Fir 9" dia., bears N.50¼°E., 39 lks. mkd. ¼ S15 BT.</p> <p> A Fir 6" dia., bears N.21½°W., 27½ lks. mkd. ¼ S16 BT.</p>
<p>Greg Lang - Nov. 2004 - C.S. File 65/52-16A</p> <p>-----</p> <p>Found - 3½" Brass cap set by BLM 26.5" Cedar (original) bears N.40°W., 22.5' 16½" D.Fir bears N.51°E., 26.0' (1972 by BLM) 10" D.Fir bears N.21°W., 17.1' (1972 by BLM)</p> <p>New - 13" D. Fir bears S.20½°W., 23.5' scribed "¼ S16 BT" 12 ½" D. Fir bears S.66°E., 22.3' scribed "¼ S15 BT"</p> <p>Note - We set and measured to spikes in the base of all bearing trees; bearings to the trees are based on BLM's 1972 survey line from the N¼ Corner to the NW Section Corner of Section 21 (S.89°41'00"W). Corner is located on a southerly slope 100' north of a dirt road.</p>
<p>Fd. Ok by Greg Lang, 1/2007 - M152-13</p>
<p>BLM visit, May 2008, Kenneth W. Saveland, no field notes or new corner report see retracement plat dated 2011</p>
<p style="text-align: right;">1</p>