

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6949)

Set a stone 16 x 10 x 7 ins., 12" in the ground for cor. to secs. 3, 4, 9 and 10, marked with 3 notches on E. and 5 notches on S. edges, from which

A Laurel 10" dia., bears N.33½°E., 98 lks. dist. mkd. T30S R3W S3 BT.

A Laurel 8" dia., bears S.80 3/4°E., 73 lks. dist. mkd. T30S R3W S10 BT.

A Fir 15" dia., bears S.83½°W., 93½ lks. dist. mkd. T30S R3W S9 BT.

A Fir 36" dia., bears N.66¼°W., 56 lks. dist. mkd. T30S R3W S4 BT.

Survey by R.H. Gee, R.E. 3723 - Wit: Joe Forrest; Norman Walker - Dec. 20, 1955 & Feb. 16, 1956 - C.S. File 42/193-1

Found - A Fir 54", N.66°W., 37.0 ft., old BT.

A Fir 30", S.83°35'W., 61.7 ft. old BT.

Drove 3/4" x 30" Iron rod in ground for corner, from which New BTs:

A Fir 30", N.35°22'E., 34.6 ft. mkd. S3 T30S R3W BT

A Madrone 12", S.56°E., 46.9 ft. mkd. S10 T30S R3W BT.

BLM Resurvey by Lynn M. Roseberry, Cadastral Surveyor - Under Group #599 Surveyed, Oct. 26, 27, 1967 - (DCSO records Vol. 34 Page(s) 14060-61)

The Sec. cor., monumented with the original conglomerate stone, 9 x 8 x 5 ins., firmly set, 4" in the ground mkd. with 3 grooves on E. and 5 notches on the S. edge, from which the remaining original bearing trees:

A sawed Fir stump 35" dia., bears S.85°W., 93½ lks. dist., with a healed blaze. (Rec. S.83½°W.)

A Fir 52" dia., bears N.64½°W., 56 lks. dist. with illegible scribe marks visible on partially opened blaze. (Rec. N.66¼°W.)

and bearing trees mkd. by Gee in 1956

A Fir 30" dia., bears N.35°E., 56½ lks. dist., with a healed blaze.

A Madrone 13" dia., bears S.61°E., 70 lks. dist., with scribe marks S10 BT visible on partially healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

(Cont. Next Page)

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

T 30 S R 3 W
S 4 | S 3
S 9 | S 10
1967

Deposit the original stone alongside the iron post.

Greg Lang - June 1993 - M 123-14

Condition Report

Found - Brass cap.

39½" Fir bears N.35°E., 56½ lks.

15" madrone bears S.61°E., 70 lks.

35" Fir stump bears S.85°W., 93½ lks.

36½" Fir bears N.64½°W., 56 lks.

43" Fir with tag dated 1942, no record, bears
approx. N.25°W., 24 ft.