

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION C C for Secs. 3 & 4 only (North bdy)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6954-55)

At point of intersection, Set a stone 16x10x10 ins., 12" in the ground, for closing cor. to secs. 3 and 4, marked C C on S. face, with 3 notches on E. and W. faces, from which
A Fir 6" dia., bears S.39¼°E., 35½ lks. dist. mkd. T30S R3W S3 BT.
A Laurel 10" dia., bears S.17¼°W., 39 lks. dist. mkd. T30S R3W S4 BT.
A Fir 6" dia., bears N.24¼°E., 12 3/4 lks. dist. mkd. T30S R3W C C S3 and 4 BT.

Survey by R.H. Gee, R.E. 3723 - Wit: Joe Forrest; Norman Walker - Dec. 20, 1955 & Feb. 16, 1956 - C.S. File 42/193-2

Found stone as described in records, from which
A Fir 14", N.24°15'E., 8.4 ft. mkd. "CC S3 and 4 BT". Old BT.
A Fir 16", S.39°15'E., 22.1 ft. mkd. "S3 BT". Old BT.
A Fir 10", S.52°30'W., 43.3 ft. mkd. "S4 T30S R3W BT". New BT.

BLM Resurvey by Lynn M. Roseberry, Cadastral Surveyor - Under Group #599 Surveyed Oct. 1967 - (DCSO records Vol. 34 Page(s) 14061-62)

(At 9.95 chs. N.0°26'E from 1/4 cor. for secs. 3 & 4)
True point for the closing cor. of secs. 3 and 4.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 29 S R 3 W
S 33
S 4 | S 3
C C
T 30 S R 3 W
1967

from which
A Fir 18" dia., bears S.49 3/4°E., 30 lks. dist., with illegible scribe marks visible on partially healed blaze. (This tree is the original SE. bearing tree)
A Fir 12" dia., bears S.56¼°W., 60½ lks. dist., with a healed blaze. (This tree was mkd. by Gee in 1955)

From this point, the original closing cor. of secs. 3 and 4, bears N.0°26'E., 0.075 chs. dist., monumented with the original conglomerate stone, 16x10x10 ins., firmly set 10" in
(Cont. Next Page)

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION C C for Secs. 3 & 4 only, (North bdy)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

the ground, mkd. with 3 notches on the E. and W. faces, and CC on the S. face, from which the original bearing trees:

A Fir snag 16" dia., bears N.24¼°E., 12 ¾ lks. dist., with scribe marks T30S R3W visible on partially healed blaze.

A Fir 18" dia., bears S.39¼°E., 35½ lks. dist., with illegible scribe marks visible on partially healed blaze.

A Madrone stump hole and clump of Madrone sprouts, bears S.17¼°W., 39 lks. dist.

and a bearing tree mkd. by Gee in 1955:

A Fir 12" dia., bears S.51°W., 65½ lks. dist., with a healed blaze.

Fd. and used in BLM Resurvey by James E. Jelley and Lynn Roseberry Cadastral Surveyors under Group #554 - Surveyed May 1966/Oct. 1967 - (DCSO records Vol. 34 Page(s) 14033)

BLM Rehabilitation by Timothy J. Moore, Cadastral Surveyor, under Group #1000, surveyed Oct. 26, 2000. (DCSO rec. Vol. 53 page(s) 20590-1)

The closing cor. of secs. 3 & 4 only, on the N. bdy. of the tp., monumented with an iron post, 2½" dia., firmly set, projecting 8" above ground, with brass cap mkd.

T 29 S R 3 W
S 33

S 4 | S 3
C C
T 30 S R 3 W
1967

from which the remains of an original bearing tree

A fir, 23" dia., bears S.49¾°E., 19.8 ft., with a healed blaze. (This tree was originally mkd. as the SE. bearing tree for the original closing cor.)

and remains of a bearing tree mkd. by Gee

A sawed and tin capped fir stump, 16" dia., bears S.56¼°W., 39.9 ft., with a healed blaze on the fallen trunk lying alongside. (This tree was mkd. as a new bearing tree for the original closing cor. Record, S.51°W., 43.2 ft.)

and a new bearing tree

A fir, 25" dia., bears S.27½°W., 102.5 ft., mkd. T30S R3W S4 BT.

The new bearing tree has a 2½ inch x ¼ inch magnetic nail (MAG-NAIL) driven at the base on the right side-center.