

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for S. 34 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6777-78) and (duplicate info. on Page 6910)

Set a Fir post 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on N. face, from which
A Maple 13" dia., bears S.66¼°E., 9 lks. dist. mkd. ¼ S BT
A Fir 5" dia., bears N.54¼°W., 47 lks. dist. mkd. ¼ S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. -
Wit: R.G. Boyd - Sept. 1958 - C.S. File 42/392-2

Determined by O.B.T.s:
28" Maple bears S.66°E., 6.0 ft. found scribe.
24" Fir bears N.54°W., 31.0 ft.
At corner point, SET 1" x 30" Iron pipe, from which
24" Maple bears N.77°E., 53.0 ft. mkd. ¼ S34 BT.
18" W.Fir bears S.73°W., 16.0 ft. mkd. ¼ S34 BT.
Sec. Cor. for 3 & 4, T31-3, bears West 441.5 ft. dist.
Stouts Creek bears East, 520.0 ft.
Road bears East, 590.0 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones &
Joe Brady, crew - Dec. 1965 - C.S. File 52/63-35

Found - Iron pipe at corner.
Orig. 13" Maple now 25" S.66¼°E., 5.9 ft., had been opened for scribe.
Orig. 5" Fir now 20" N.54¼°E., 31.0 ft., shows scar.
19" Fir S.73°W., 16.0 ft., shows parts of scribing.
18" Maple N.77°E., 53.0 ft. scribed ¼ S34 BT.

Set Brass cap alongside Iron pipe at corner marked:

County Surveyors Office
T30S R3W
S 34
¼ T31S R3W
1965

Fd. OK, Aug. 1983 by H. Johnstone - M 95-6
FD. 1965 BC & BTs by T. Hostetter - M170-20