

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6884)

Set ¼ sec. post, from which
A Laurel 12" dia., bears S.2°W., 35 lks. dist.
A Fir 20" dia., bears N.70°E., 55 lks. dist.

Douglas Co. Surveyors office - John M. Powell, Deputy - Frank Jones; Joe Brady, crew - March 1968 - C.S. File 54/52-11

Found - 39" D.Fir, now stump, N.70°E., 36.3 ft., tree opened, "S" visible, open for "BT". Ring count places D.Fir face approx. 98 years.

No trace of Laurel SW.

Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 3 W

¼ S 27
S 34
1968

New BTs- 20" laurel N.60°E., 80.6 ft. mkd. ¼ S27 CS BT.
55" D.Fir N.82°E., 46.0 ft. mkd. ¼ S27 CS BT.

No trees for good control in the South quad.

This corner lies on steep South slope approx. 350 ft. N. of Milo store and post office.

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - John Powell, Randy Smith, crew - March 1983 - C.S. File 62/7-11

Recent slide activity had destroyed previous monument.
Found - Orig. 20" Fir now 39" stump, with scribed "S BT" visible in previously opened blaze.

20" now 24" Madrone with scribed "¼ S27 CS BT" visible in partially healed blaze.

55" Fir now 55" stump with scribed "S27" visible in partially healed blaze.

On March 3, 1983, my crew set a 1" x 30" I.P. with brass cap using record bearings and distances from the found bearing trees. Cap mkd. "Douglas Co. Surveyors Office T30S R3W ¼ S27 S34 1983." Bearing trees are as follows:

39" Fir stump bears N.70°E., 36.3 ft.

24" Madrone bears N.60°E., 80.6 ft.

55" Fir stump bears N.82°E., 46.0 ft.

Since the brass cap falls in the center of the slide area and will probably be washed out again, I returned March 23, 1983 and set two 5/8" iron rods with alum. caps as reference marks.

New Accessories:

(Cont. Next Page)

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

5/8" x 30" iron rod with alum. cap stamped "Douglas
Co. Surveyor RM S27", bears N.45°W., 39.5 ft.
5/8" x 30" Iron rod with alum. cap stamped "RM S34
Douglas Co. Surveyor", bears S.45°W., 30.0 ft.
Sketch in C.S. File.

Fd. Ok by K. DeGroot, 12/2007 - M146-67
Fd BC as per rec. 12/2016, R Brown, M173-6