

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6948)

Set a stone 11 x 10 x 5 ins., 7" in the ground for ¼ sec. cor. marked ¼ on N. face, from which

A Fir 36" dia., bears N.55¼°W., 24 lks. dist. mkd. ¼ S BT.

A Fir 14" dia., bears S.56½°W., 32 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Jan. 1963 - C.S. File 52/138-12

Found - Stump section of NW. BT.

Orig. 14" now 18" Fir snag, shows good scribing on old face.

Corner stone not found.

Set Brass cap at cor. mkd: County Surveyors Office

T 30 S R 3 W

¼ S 10

S 15

1963

New BTs- 24" Laurel bears S.59°W., 53.2 ft. scribed ¼ S15 CS BT.

16" Laurel bears N.73°W., 65.5 ft. scribed ¼ S10 CS BT.

Mark Smalley for Roseburg Resources, Feb. 1998 - M 128-45

Found - 1963 County Brass cap on iron pipe.

28" Laurel, S.59°W., 53.2 ft., healed

21" Laurel, N.73°W., 65.5 ft., healed

Duffy root crown, S.56½°W., 21.1 ft., original

New Accessories -

12" Fir, S.24°E., 5.0 ft. scribed "S 15 BT"

6" Fir, N.2°W., 11.8 ft. scribed "S 10 BT"