

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6950)

-----  
Set a Cedar post 4 ft. long, 4" sq., 24" in the ground for 1/4 sec. cor. marked 1/4 S. on N. face, from which

A Fir 8" dia., bears N.70 1/2°E., 14 1/2 lks. dist. mkd. 1/4 S BT.

A Fir 13" dia., bears S.33 1/2°E., 82 lks. dist. mkd. 1/4 S BT.

-----  
Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Jan. 1963 - C.S. File 52/138-4

-----  
Found - Orig. 8" now 22" Fir N.70 1/4°E., 9.6 ft. We open and find good scribing "B".

Find stump of orig. SE. BT.

Set Brass cap at cor. mkd: County Surveyors Office

T 30 S R 3 W

1/4 S 3  
S 10

1963

New BTs- Rescribe orig. now 22" Fir N.70°E., 10.2 ft. 1/4 S3 CS BT.

13" R.Fir bears S.6°W., 41.3 ft. scribed 1/4 S10 CS BT.

-----  
Mark Smalley for Roseburg Resources, Feb. 1998 - M 128-45

-----  
Found - 1963 County Brass cap on iron pipe  
30" Fir, N.70°E., 10.2 ft. - healed opened orig.  
22" Fir, S.6°W., 41.3 ft. - healed

New Accessories -

15" double Fir, N.1°E., 58.2 ft. scribed "1/4 S BT on west trunk

5" Fir, N.66°W., 9.9 ft. scribed "BT"

5" Fir, S.16°E., 27.1 ft. scribed "BT"

-----  
Fd. Ok 2/2012 by R. Quimby - C.S. File 65/76-27