

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 444700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 34 only, T29-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6319)

Marked Fir, 36" dia., for ¼ sec. cor., from which
A Fir tree 24" dia., bears S.40°W., 23 lks.
A Fir 36" dia., bears N.15°W., 19 lks.

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6953)

The ¼ sec. cor. which is a Fir tree 36" dia., marked ¼ S. on N. side, from which
A Fir 24" dia., bears S.40°W., 23 lks. dist., mkd. ¼ S BT
This tree is dead. In it's stead, I mark a Cedar 7" dia., which bears S.36°E., 54 lks. dist., mkd. ¼ S BT.
A Fir 36" dia., bears N.15°W., 19 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Dec. 1962 - C.S. File 52/126-94

Found both BTs and corner tree as recorded. Corner tree and NW. BT are good log trees and could now be cut.
Set Brass cap 4.0 ft. North of center of corner tree and mkd. "County Surveyors Office, 1962 Wit. Cor. 4' South to S¼ S34 T29S R3W".
New BT - 14" R.Fir bears N.31°W., 54.5 ft. scribed W.C. ¼ S34 CS BT.
Orig. now 26" Cedar bears S.30°E., 39.3 ft., shows good scar.

BLM Resurvey by James E. Jelley and Lynn Roseberry Cadastral Surveyors under Group #554 - Surveyed May 1966/Oct. 1967 - (DCSO records Vol. 34 Page(s) 14031-32)

The ¼ sec. cor. of sec. 34 only, on the S. bdy. of the Tp., occupied by the original corner tree, a Fir 42" dia., with scribe marks ¼ visible on opened blaze on N. side, from which the original bearing trees;
A Fir 40' dia., bears N.13°W., 22 lks. dist., with illegible scribe marks visible on opened and burned blaze. (Rec. N.15°W. 19 lks.)
A Fir snag 24" dia., bears S.37°W., 26 lks. dist., bark scribed ¼ S BT. (Rec. S.40°W., 23 lks.)
and a bearing tree mkd. by Bushey in 1893
(Cont. Next Page)

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 444700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 34 only, T29-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Cedar 27" dia., bears S.36°E., 54 lks. dist., mkd. with a healed blaze.
and a bearing tree mkd. by Byron in 1962
A Fir 18" dia., bears N.30°W., 87 lks. dist. mkd. with a healed blaze.

From this point, a witness corner established and recorded by Byron in 1962, bears N.13°W., 0.06 chs. dist., monumented with an iron post, 1" dia., firmly set, extending 16" above ground with brass cap mkd: COUNTY SURVEYORS OFFICE
T 29 S R 3 W
South
1/4 S 34
W C
T 30 S
1962

Fd. Ok by Ronald L. Rice 10/2004 - M 145-76

Ronald L. Rice, Ward NW - For: Seneca Jones Timber Co. - 10/2004 - M 145-76

Found - Corner tree 48" D.Fir with healed face on North side with the following accessories;
WC 1/4 County Surveyors 2 1/2" brass cap dated 1962 bears N.13°W., 4.0'
All other accessories down either down or burned
New BTs- 16" D.Fir bears S.16°E., 18.8' - blazed, scribed "xBT"
31" D.Fir bears N.83°E., 46.5' - blazed, scribed "1/4 S34 BT"

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 01/9/2025 - C.S. File 67/59-45

Found - 48" D.fir corner tree healed face N. side DCSO brass cap W.C. N.13°W. 4.0'. Cap MKD
COUNTY SURVEYORS
T29S R3W
→ 4 SOUTH
1/4 S34
WC
T30S
1962 OFFICE
Reference to true corner brass cap witness corner N.13°W. 4.0'.
21" D. fir S.16°E. 18.8' fully healed low blaze add 3 1/2" mag nail right side, center. Cont.

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 444700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 34 only, T29-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

33" D.fir N.83°E. 46.5' fully healed single blaze
add 3½" mag nail right side, center.
Metal post west edge of tree.
New - Reference to Witness corner.
N.E. tree N.86½°E. 46.0'.
S.E. tree S.13°E. 22.9'.
New bearing trees to W. corner.
16" I.Cedar S.48°W. 17.0' scribed "X" CSBT on double
blaze 3½" mag nail right side center.
12" D.fir N.55°W. 26.8' scribed ¼ S34 on double
blaze 3½" mag nail right side, center.
Metal post S.35°W. 4.0'.
Notes - Mon is approx 170' south of gravel road on south
edge of clear cut on north edge of older reprod
Compass decl. 14¼°E.
O CRS COORDINATE SYSTEM
COTTAGE GROVE-CANYONVILLE ZONE
N 60488.363 E 239683.935