

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6932)

Set a Maple post 4 ft. long 4" sq., 24" in the ground, for ¼ sec. cor. mkd. ¼ S. on W. face, from which
A Cedar 30" dia., bears N.42°E., 36 lks. dist. mkd. ¼ S BT
A Fir 18" dia., bears S.37°W., 8½ lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Sept. 1967 - C.S. File 54/52-2

Found - Orig. 18" Fir, now down and rotten, S.37°W., 5.6 ft. scribe found "/" "S" "BT".
Orig. 30" Cedar now down, burnt and rotten, N.42°E., 23.8 ft., mark found in tree which looks like scribe.

Set Brass cap at ¼ cor. mkd: County Surveyors Office
T 30 S R 3 W
¼ S 22 | S 23
1967

New BTs- 7" D.Fir S.86°W., 13.8 ft. mkd. ¼ S22 CS BT.
6" D.Fir S.41°E., 12.6 ft. mkd. ¼ S23 CS BT.

BLM visit, May 2008, Kenneth W. Saveland, no field notes or new corner report see retracement plat dated 2011

James Klein & Richard Kitz - For: Pacific Connector Gas Pipeline Project/Williams - Sept. 2014 - M166-19 A-E

Found - 2½" brass cap stamped County Surveyors Office 1967
BTs - 20" Pine with healed face and tag dated 9/67;
S.86°W., 13.8' to nail side center
18" Fir with healed face and tag dated 9-67;
S.41°E., 12,6' to nail side center

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2813, surveyed Sept 2015/April 2017 - (DCSO records Vol. 58 Page 23495-6)

The ¼ sec. cor. of secs. 22 & 23, monumented with an iron post, 1¼" dia., firmly set, projecting 8" above ground with brass cap (properly) mkd.
from which the remains of the original bearing trees reported by Saveland in 2008
A root hole bears N.42°E., 23.8 ft., with a fallen, burnt cedar trunk, size indeterminate, lying alongside, with no marks visible.

continued next page

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A decayed fir stump, size indeterminate, bears S.37°W.,
5.6 ft., with no marks visible.

and the remains of the bearing trees mkd. by the Douglas
County Surveyor's Office in 1967, reported by Saveland

A fir, 23" dia., bears S.44 $\frac{3}{4}$ °E., 12.6 ft., with a healed
blaze.

A sawed fir stump, 21" dia., bears S.81 $\frac{3}{4}$ °W., 13.4 ft.,
with a healed blaze.

and a new bearing tree

A fir, 17" dia., bears N.70 $\frac{1}{4}$ °W., 42.4 ft., mkd. $\frac{1}{4}$ S22 BT.

Each new BT has a 2 $\frac{1}{2}$ "x $\frac{1}{4}$ " magnetic nail (Mag Nail) driven at
the base right side-center & has a magnet deposited in a
white plastic case at the base of the stainless steel post.
Alum. angle iron driven alongside each corner.

Corner is located on a S. slope.