

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Pgs 6932-33)

Set a stone 13 x 13 x 4 ins., 9" in the ground, for cor. to secs. 14, 15, 22 and 23, marked with 2 notches on E. and 3 notches on S. edges, from which

A Fir 8" dia., bears N.37 3/4°E., 26 lks. dist. mkd. T30S R3W S14 BT.

A Fir 29" dia., bears S.10½°E., 30 lks. dist. mkd. T30S R3W S23 BT.

A Fir 12" dia., bears S.50°W., 74 lks. dist. mkd. T30S R3W S22 BT.

A Fir 28" dia., bears N.45°W., 29 lks. dist. mkd. T30S R3W S15 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Sept. 15, 1960 - C.S. File 42/392-67

Determined by O.B.T.s:

30" Fir snag S.10°E., 19.8 ft., found scribe.

38" Fir snag, N.45°W., 19.2 ft., found scribe.

14" Fir snag, S.50°W., 48.8 ft., found scribe.

At corner point, found stone and Set 3/4" x 30" Iron rod, from which

14" Fir bears S.24°W., 55.6 ft. mkd. S22 R3W X BT.

3" Fir S.18°W., 15.9 ft. mkd. S22 BT.

3" Fir S.58°W., 7.6 ft. mkd. S22 BT.

2" Fir N.74°E., 6.3 ft. mkd. S14 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Nov. 1967 - C.S. File 54/52

Found - Orig. 30" Fir snag, face burnt, S.10°E., 19.8 ft.

Orig. 38" Fir snag, face burnt, N.45°W., 19.2 ft.

14" now 16" D.Fir S.24°W., 56.6 ft. "BT" visible.

3" D.Fir now burnt, S.18°W., 15.9 ft., shows scar.

3" D.Fir now burnt, S.58°W., 7.6 ft. shows scar.

2" D.Fir now burnt, N.74°E., 6.3 ft. shows scar and part of scribing.

1" iron pipe at section corner.

New BTs- 48" D.Fir S.10°W., 80.3 ft. mkd. T30S R3W S22 CS BT.

14" D.Fir S.52°W., 74.7 ft. mkd. T30S R3W S22 CS BT.

Corner now falls in burn, no other trees within reason to scribe. Corner lies on steep West slope approx. 40.0 ft. North of small ravine.

(Cont. Next Page)

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. cor. for 14, 15, 22 and 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM resurvey by Stephen D. Albright and Jack W. Bowder, Cadastral Surveyors, under Group #776, surveyed June/July 1972 - (DCSO records Vol. 36 Page(s) 14978-79)

The Sec. cor., perpetuated and recorded by Markham in 1960, monumented with an iron rod 3/4" dia., firmly set, extending 5" above ground, from which the remains of the original bearing trees:

A burned Fir stump 30" dia., bears S.10½°E., 30 lks. dist., no marks visible.

A decayed Fir stump size indeterminate, bears S.50°W., 74 lks. dist., no marks visible.

A burned Fir snag 38" dia., bears N.45°W., 29 lks. dist. no marks visible.

and bearing trees mkd. by Markham:

A root hole bears S.18°W., 24 lks. dist., with a down Fir alongside, 3" dia., with healed blaze.

A Fir 15" dia., bears S.24°W., 83½ lks. dist., with partial scribe marks visible on pitched over blaze.

A Fir snag 3" dia., bears S.58°W., 11 lks. dist. with healed blaze.

and unrecorded bearing trees: (See above)

A Fir 55" dia., bears S.11°W., 121 lks. dist. with scribe marks 30S 3W S2 SBT visible on partially healed blaze.

A Fir 17" dia., bears S.50°W., 112 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 20" in the ground, with brass cap mkd:

T 30 S R 3 W
S 15 | S 14
S 22 | S 23
1972

from which a new bearing tree

A Fir 49" dia., bears N.41½°E., 188½ lks. dist. mkd. T30S R3W S14 BT.

Reset iron rod alongside iron pipe.

Douglas Co. Surveyors Office - Gary Langliz; R.B. Kimberling, crew - April 27, 1977 - C.S. File 59/31-34

Found - 1" I.P. with flagging laying downhill 20 ft. (West) of corner.

A burned orig. 29" now 30" Fir stump at record S.10½°E., 19,8 ft. No marks visible, we opened an apparent blaze and found scribe marks "BT."

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

An orig. 28" now 32" burned Fir snag bears N.45°W., 19.1 ft. We opened apparent blaze and found scribe marks "BT"

A Fir orig. 14" now 15", bears S.26°W., 55.8 ft. (Rec. S.24°W. 55.6 ft.), badly barked on East side and burned, with partial scribe marks visible on pitched over blaze.

A Fir 17", bears S.52°W., 75.7 ft. (Rec. S.50°W., 73.9 ft.) with fragmentary scribe marks visible on partially healed blaze.

A Fir 49" bears N.41½°E., 189.6 ft. (Rec. 124.4 ft.) single blazed and scribed "T30S R3W S14 BT"

Set an I.P., 30" long, 2" dia., 20" in the ground with brass cap mkd: Douglas County Surveyor T30S S15 S14 S22 S23 R3W 1977.

Corner is on a 33° westerly slope 40 ft. North of draw in logged off unit.

BLM Corrective Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, under Group No. 2134, surveyed March/April 2006 - (DCS0 records Vol. 56 Page(s) 22102-3)

The cor. of secs. 14, 15, 22, & 23, perpetuated by Markham, in 1960, and by the Douglas County Surveyors Office in 1967, and remonumented by the Douglas County Surveyors Office in 1977, monumented with an iron post, 2" dia., firmly set, projecting 1" above ground, with brass cap (properly) mkd. from which the remains of the original bearing trees

A sawed, decayed fir stump, 30" dia., bears S.10½°E., 19.8 ft., with no marks visible.

A roothole bears S.50°W., 48.8 ft., with uprooted fir stump, size indeterminate, lying downhill, with no marks visible.

A sawed, burnt, decayed fir stump, 26" dia., bears N.45°W., 19.1 ft., with no marks visible.

and remaining BT mkd by Markham, reported by Albright & Bowder

A fir, 20" dia., bears S.24°W., 55.1 ft., with a healed blaze.

and remains of BTs mkd. by the Douglas County Surveyors Office in 1967, reported as unrecorded by Albright and Bowder

A roothole bears S.11°W., 79.9 ft., with no remains of the trunk located.

A fir, 21" dia., bears S.52½°W., 75.4 ft., with a healed blaze. (Record, S.50°W., 73.9 ft.)

and remains of a bearing tree mkd. by Albright and Bowder

continued next page

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A sawed fir stump, 42" dia., bears N.39½°E., 189.6 ft., with scribe marks 30S 3W S14 BT visible on a partially healed blaze. (Record, N.41½°E., 124.4 ft.)
and new bearing trees
A fir, 11" dia., bears N.49¾°E., 27.7 ft., mkd. T30S R3W S14 BT.
A fir, 7" dia., bears S.46¾°E., 32.2 ft., mkd. T30S R3W S23 BT.
A fir, 10" dia., bears N.72¾°W., 16.0 ft., mkd. T30S R3W S15 BT.
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.
The geographic position (NAD 1983 (CORS 96)) of the following corners were determined by a direct tie to a temporary point for which a position had been determined, to an accuracy level of 0.050 meters or better, 95% confidence level, relative to the National Spatial Reference System stations noted above.
The corner of sections 14, 15, 22, and 23:
Latitude: 42°57'37.72" N. Longitude: 123°02'29.13" W.

BLM visit, May 2008, Kenneth W. Saveland, no field notes or new corner report see retracement plat dated 2011

James Klein & Richard Kitz - For: Pacific Connector Gas Pipeline Project/Williams - Sept. 2014 - M166-19 A-E; revised by M166-45 A-E

Found - 2½" brass cap stamped County Surveyor 1977
BTs - 11" Fir with visible scribes and BLM tag dated 2008; N.49¾°E., 27.7' to nail side center
7" Fir with visible scribes and BLM tag dated 2008; S.46¾°E., 32.2' to nail side center
10" Fir with visible scribes and BLM tag dated 2008; N.72¾°W., 16.0' to nail side center

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2813, surveyed Sept 2015/April 2017 - (DCSO records Vol. 58 Page 23497-8)

The cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 1¼" dia., firmly set, flush with ground, with brass cap (properly) mkd.
from which the remains of the original bearing trees reported by Saveland in 2008
A sawed, decayed fir stump, 28" dia., bears S.10½°E., 19.8 ft., with no marks visible.
continued next page

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A root hole bears S. 50°W., 48.8 ft., alongside of which is a sawed, decayed, and uprooted fir stump, size indeterminate, with no marks visible.

A sawed, burnt, decayed fir stump, 26" dia., bears N.48½°W., 19.1 ft., with no marks visible.

and a bearing tree mkd. by Markham, PE No. 2880, in 1960, reported by Saveland

A fir, 24" dia., bears S.24°W., 55.1 ft., with a healed blaze.

and the remaining bearing tree mkd. by the Douglas County Surveyor's Office in 1967, reported by Saveland

A fir, 27" dia., bears S.52½°W., 75.4 ft., with a healed blaze.

and the remains of a bearing tree mkd. by Albright and Bowder in 1972, reported by Saveland

A sawed fir stump, 47" dia., bears N.39½°E., 189.6 ft., with scribe marks T30S R3W S14 BT visible on a partially healed blaze.

and the BTs mkd. by Skeesick in 2006, reported by Saveland

A fir, 13" dia., bears N.49¾°E., 27.7 ft., with a healed blaze.

A fir, 8" dia., bears S.46¼°E., 32.2 ft., with a healed blaze.

A fir, 10" dia., bears N.72¼°W., 16.0 ft., with a healed blaze.

Corner is located on a SW. slope.