

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6935)

Set a stone 16 x 9 x 5 ins., 12" in the ground for cor. to secs. 10, 11, 14 and 15, marked with 2 notches on E. and 4 notches on S. edges, from which

- A W.Fir 7" dia., bears N.66°E., 24 lks. dist. mkd. T30S R3W S11 BT.
- A Fir 18" dia., bears S.39½°E., 97 lks. dist. mkd. T30S R3W S14 BT.
- A Fir 8" dia., bears S.33 3/4°W., 64 lks. dist. mkd. T30S R3W S15 BT.
- A Cedar 18" dia., bears N.28½°W., 49½ lks. dist. mkd. T30S R3W S10 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Jan. 1963 - C.S. File 52/138-13

Found - Stone at corner as recorded.
Orig. 18" now 26" Fir, S.40°E., 64.0 ft., shows good scar.
Orig. 7" now 18" Fir stump N.16°E., 15.8 ft., shows scar.
Orig. 18" now 30" Cedar N.28½°W., 33.0 ft., down, shows scar.
Orig. SW. BT, not found.

Set brass cap alongside cor. stone and marked:
County Surveyors Office

T 30 S R 3 W
S 10 | S 11
S 15 | S 14
1963

- New BTs- 12" R.Fir bears S.66°W., 14.7 ft. scribed S15 T30S R3W CS BT.
- 10" R.Fir bears N.85½°W., 36.3 ft. scribed S10 T30S R3W CS BT.
- 18" Maple bears N.30°E., 20.6 ft. scribed S11 T30S R3W CS BT.

Mark Smalley for Roseburg Resources, Feb. 1998 - M 128-45

Found - 1963 County Brass cap on I.P. w/stone alongside.
30" Fir, S.40°E., 64.0 ft.- healed diseased orig.
Pile of duff, N.16°E., 15.8 ft. - orig.
24" Fir, S.66°W., 14.7 ft. - healed
19" Fir, N.85½°W., 36.3 ft. - healed
18" Maple, N.30°E., 20.6 ft. - down, rotten
Continued on next page

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New Accessories -

12" Fir, S.38°E., 59.4 ft. scribed "S 14 BT"

10" Fir, S.80°E., 27.2 ft. scribed "S 14 BT"

Fd. Ok by R. Quimby, 7/11/2012 - C.S. File 65/77-9