

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 CORNER FOR SECTIONS 10 & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6937)

Set a Fir post, 4 ft. long, 4 ins. sq., 24" in the ground, for ¼ sec. cor., marked 1/4S on W. face, from which:
 A Fir, 26" dia. bears N.47½°W., 19 lks. dist.
 marked "1/4 S BT"
 A Fir, 10" dia. bears N.21½°E., 67½ lks. dist.
 marked "1/4 S BT"

Mark Smalley for Roseburg Resources, Feb. 1998 - M 128-45

Set - 5/8" x 48" iron rod & alum. cap marked "LS 2354 1998"
New Accessories -
 8" Fir, N.68°W., 1.6 ft. scribed "1/4 S BT"
 10" Fir, S.40°E., 14.1 ft. scribed "1/4 S BT"
 9" Fir, S.10°E., 18.4 ft. scribed "1/4 S BT"
 12" Fir, S.43°W., 14.0 ft. scribed "C 1/4 BT"

Fd. Ok 2/2012 by R. Quimby - C.S. File 65/76-27