

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Sec Cor for 2, 3, 10 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCS0 records Vol. 16 Page(s) 6937)

Set a stone 13 x 8 x 5 ins., 9" in the ground for cor. to secs. 2, 3, 10 and 11, marked with 2 notches on E. and 5 notches on S. edges, from which

A Laurel 10" dia., bears N.65°E., 33 lks mkd. T30S R3W S2 BT.

A Fir 8" dia., bears S.58½°E., 28 lks mkd. T30S R3W S11 BT

A Laurel 8" dia., bears S.52°W., 38¼ lks. mkd. T30S R3W S10 BT.

A Fir 9" dia., bears N.31¼°W., 104 lks mkd T30S R3W S3 BT

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - July 25, 1960 - C.S. 49/47-14

Found - Stake at corner.

Orig. 8" now 24" Fir S.58½°E., 18.5 ft., shows good scar, I do not open.

Orig. 9" now 26" R.Fir N.31¼°W., 68.6 ft., shows good scar, I do not open.

Orig. 8" Laurel now 12" stump cut high, I open and find good scribing "3", S.52°W., 25.2 ft. We measure 23.2 ft.

Orig. NE. BT not found.

Set brass cap alongside corner stake marked:

County Surveyors Office

T 30 S R 3 W

S 3 | S 2

S 10 | S 11

1960

New BTs- 12" R.Fir bears S.8°W., 24.4 ft. scribed S10 T30S R3W CS BT.

17" R.Fir bears N.18°E., 6.5 ft. scribed S2 T30S R3W CS BT.

Mark Smalley for Roseburg Resources, Feb. 1998 - M 128-45

Found - 1960 County brass cap on iron pipe
32" Fir, S.58½°E., 18.5 ft. - healed, orig.
34" protected stump, N.31¼°W., 68.6 ft. orig.
18" Fir, S.8°W., 24.4 ft. - healed
24" Fir, N.18°E., 6.5 ft. - healed

New Accessory -
13" Fir, N.89°W., 12.2 ft. scribed "S 3 BT"

Fd. Ok 2/2012 by R. Quimby - C.S. File 65/76-27