

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6936)

Set a stone 14 x 14 x 3 ins., 10" in the ground, for 1/4 sec. cor. marked 1/4 on N. face, from which
A Fir 28" dia., bears N.30 1/2°E., 36 lks. dist. mkd. 1/4 S BT
A Fir 5" dia., bears S.5 1/4°E., 28 lks. dist. mkd. 1/4 S BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Jan/Feb. 1963 - C.S. File 52/138

Found - Orig. 28" now 44" Fir, N.30°E., 26.7 ft., shows scar.
Orig. 5" now 13" Fir, S.5°E., 18.7 ft. shows scribing.

Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 3 W
1/4 S 11
S 14
1963

Rescribe now 13" Fir, S.5°E., 18.7 ft. "1/4 S14 CS BT."

Fd. Ok by R. Quimby, June 2013 - C.S. File 65/78-45