

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6938)

A Fir 15" dia., which I mark ¼ S. on N. face, for ¼ sec. cor., from which

A Fir 18" dia., bears S.41½°W., 10½ lks. dist. mkd. ¼ S BT

A Fir 6" dia., bears N.78°E., 25 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - July 25, 1960 - C.S. 49/47-17

Found - Corner tree, previously opened, shows good scribing "4".

Orig. 18" now 40" Fir, S.41½°W., 7.0 ft., shows good scar. I do not open.

Orig. SE. not found.

Set brass cap at corner and at West edge of corner tree mkd:

County Surveyors Office

T 30 S R 3 W

¼ $\frac{S \ 2}{S \ 11}$

1960

Corner tree and BT are good lumber trees so I mark:

New BTs- 6" R.Fir bears N.30°W., 27.5 ft. scribed ¼ S2 CS BT

6" R.Fir bears S.64°W., 31.4 ft. scribed ¼ S11 CSBT

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2896, surveyed Nov 2017/Dec 2019- (DCSO records Vol. 59 Page 23796-7 & Plat T30-3 2020-1)

The ¼ sec cor. of secs 2 & 11, perpetuated by Byron, in 1960; occupied by the remains of the orig. cor. tree, a heavily decayed fir stump, 27" dia., with no marks visible, from which the remains of an original bearing tree

A decayed fir snag, size indeterminate, bears S.41½°W., 6.9 ft., with a healed blaze.

and a reference monument mkd. by Byron

An iron post, 1¼" dia. firmly set, projecting 18" above ground, bears N.15°57'09"W., 0.91 ft with a brass cap mkd. COUNTY OFFICE SURVEYORS T30S R3W ¼ S2 S11 1960.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, with brass cap mkd. T30S R3W

¼ $\frac{S \ 2}{S \ 11}$

2017

continued next page

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which
A fir, 9" dia., bears S.32°W., 23.6 ft. mkd. ¼ S11 BT.
A fir, 7" dia., bears N.13¾°W., 9.6 ft. mkd. ¼ S2 BT.
At the request of the Douglas County Surveyor's Office,
removed the brass cap from the iron post, leaving the iron
post in its original position, and place a yellow plastic
cap, 1½" dia. inside the iron post, mkd. COUNTY SURVEYOR.
Buried the brass cap alongside the true point.
NAD 1983 (2011)
Latitude 42°59'23.13N. Longitude 123°01'54.26W.