

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 542700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 35 only, T29-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page 6320)

-----  
Set Alder post for ¼ sec. cor., from which  
A Laurel 8" dia., bears N.30°E., 50 lks.  
A Laurel 8" dia., bears S.5°E., 24 lks.

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6940)

-----  
The ¼ sec cor which is a post, 4" sq w/mks nearly obliterated I remove this post & set a new post, 4 ft long, 4" sq., 24" in the ground, for ¼ sec cor. marked ¼ S. on N. face, from which  
A Laurel 8" dia., bears S.5°E., 24 lks. dist. mkd. ¼ S BT.  
A Laurel 8" dia., bears N.30°E., 50 lks. dist. mkd. ¼ S BT

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey and Clete Putnam, crew - July 1960 - C.S. 49/47-16

-----  
Found - Orig. 6" now a down 10" Laurel, N.30°E., 33.0 ft. I open and find good scribe marks "¼B". This BT was found downhill about 30.0 ft. We found matched stump section which fixed location of BT.  
Orig. SE. BT not found.  
Set brass cap at corner and alongside 14" R.Fir (East side) mkd. "County Surveyors Office 1960 South 1/4 S35 T29S R3W"  
New BTs- 10" R.Fir bears N.44½°E. 15.0 ft scribed ¼ S35 CS BT  
11" R.Fir bears N.65°W., 5.8 ft. scribed ¼ S35 CS BT  
5/8" Iron rod set by Shaner on M 17-51 for the No. 1/4 Cor. S2 T30S R3W, bears N.87°W., 76.5 ft.

Fd. OK H. Johnstone, 10/1980 - M86-6

Ron Quimby - 2/2012 - C.S. File 65/76-24

-----  
Found - DCSO Brass Cap on IP 10" above ground along side 16" D.Fir stump, in good condition.  
14" D.Fir stump 6' high w/good scar N.44°E. 15.0 ft  
New BTs- 7" D.fir N.58°E., 10.1 ft. scribed ¼ S35 BT on single face.  
8" D.Fir N.9°W., 20.3 ft. scribed ¼ S35 BT on single face.  
12" D.Fir N.41°W., 17.0 ft. scribed ¼ S35 BT on single face.  
6" fir N.24°E., 14.4 ft. scribed X @ breast high BT @ base.  
Note - Corner is on a steep facing east slope approx. 400' east of road.