

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 35 and 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6921)

-----  
Set a stone 12x12x4 ins., 8" in the ground for 1/4 sec. cor. mkd. 1/4 on W. face, from which

A Fir 20" dia., bears S.66 3/4°E., 23 lks. dist. mkd. 1/4 S BT.

A Pine 30" dia., bears N.63 1/2°W., 56 lks. dist. mkd. 1/4 S BT

-----  
Douglas Co. Surveyors Office - A. Vic Cangie; Jim Cook; Karen Cheney, crew - Sept. 2, 1976 - C.S. File 59/24-8

-----  
Found - A 20" now 35" Fir bears S.66 3/4°E., 15.2 ft. Tree has been previously opened but shows no scribing. Alive and well.

A 30" now 50" Pine bears N.63 1/2°W., 37.0 ft. Tree has been previously opened and shows "1/4" on old face. Alive and well.

A 2" wooden post at the corner point. Did not find orig. stone.

Set a 1" x 30" Iron pipe with brass cap stamped:

Douglas Co. Surveyor

T 30 S R 3 W

S 35 | S 36

1/4

1976

-----  
Fd. and used in BLM resurvey by Wayne L. Rogers; Lance J. Bishop; James L. White, Cadastral Surveyors, under Group #1133 - Surveyed June 7, 1983/Dec. 12, 1984 - (DCSO records Vol. 47 Page(s) 17852)