

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCS0 records Vol. 16 Page(s) 6887)

-----  
Set ¼ sec. post, from which  
A Fir 24" dia., bears N.2°W., 210 lks. dist.  
A Fir 15" dia., bears N.5½°E., 197 lks. dist.

N.E. Richardson; E.W. Woodford - Aug. 4, 1943 (No record source shown)

-----  
W.Oak 12" bears N.30°W., 97.0 ft.  
Fir 36" bears S.75°E., 303.7 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Jan. 1963 - C.S. File 52/138-17

-----  
Found - 12" now 16" W.Oak N.27°W., 97.0 ft., not N.30°W., shows scribing. (Richardson BT)  
36" now 44" R.Fir S.72°E., not S.75°E, 30.3 ft, shows scar. (Richardson BT)

Corner falls in field.  
Set Witness Corner 18.0 ft. North, mkd. brass cap "County Surveyors Office 1963 W.C. 18' South to ¼ S26/S25 T30S R3W"  
New BTs- Rescribe now 16" W.Oak N.33°W., 81.5 ft. "WC ¼ S26 CS BT"  
14" R.Fir bears N.35°E., 84.4 ft. scribed "W.C. ¼ S25 CS BT."

Fd. BC per rec. by Raymond Brown, 2/2007 - M152-60

Property Line Surveying - James Terrel - 8/2025 - M185-45

-----  
Found - Brass cap is missing and pipe is bent northwesterly.