

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol 16 Pages 6923-24)

Set a Hemlock post 4 ft. long, 4" sq., 24" in the ground for 1/4 sec. cor. mkd. 1/4 S. on W. face, from which
A Hemlock 8" dia., bears N.72°E., 6 1/2 lks. mkd. 1/4 S BT.
A W.Fir 14" dia., bears S.48 3/4°W., 20 lks. mkd. 1/4 S BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - March 1962 - C.S. File 49/47-28

Found no original bearing trees. Corner is 15 ft. East of logging road and in fill area. We do find orig. 20" now 27" Cedar stump with butt log section laying North and South with 2 old notches on North face. This is line tree 2.05 chs. South of corner. Find 2" x 2" Fir stake bears N.25°E., 5.0 ft. mkd. 1/4 S13 S14.

Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 3 W
1/4 S14 | S13
1962

New BTs- 14" Hemlock bears N.25°E. 35.0 ft scribed 1/4 S13 CSBT
6" W.Fir bears S.72 1/2°W., 51.2 ft scribed 1/4 S14 CS BT

Ronald L. Rice, Ward NW - For: Seneca Jones Timber Co. & Roseburg Forest Products - Jan. 2009 - M 158-53

Found - 2 1/2" DC BC dated 1962 disturbed & out of position*.
New - Reset corner & added the following accessories:
11" D.Fir bears S.85°E., 16.4' - blazed, scribed "1/4 S13 BT"
33" D.Fir bears N.36°E., 53.8' - blazed, scribed "1/4 S13 BT"
10" D.Fir bears N.21 1/2°W., 40.4' - blazed, scribed "1/4 S14 BT"
15" D.Fir bears S.35°W., 16.1' - blazed, scribed "1/4 S14 BT"

Set 1 1/4" yellow plastic cap marked "54633LS" on 5/8"x30" rebar in 27" cedar stump (1893 GL0 line tree) bears S.1°23'29"E. 135.30'

*Narrative: This corner was fd disturbed & out of position due to an uprooted fir. The only accessory recovered from the 1962 county remonumentation was the 1893 GL0 20" Cedar line tree stump 2.05 chs South. To reset the brass cap, I held the SE corner of Sec. 14 & the center of the cedar line tree stump, then projected line through said stump the rec. 2.05 chs

Fd. Ok by R. Quimby, June 2013 - C.S. File 65/78-45