

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6927-28)

Set a stone 14 x 10 x 5 ins., 10" in the ground, for ¼ sec. cor. mkd. ¼ on W. face, from which
A Fir 4" dia., bears N.64°W., 8½ lks. dist. mkd. ¼ S BT.
A Laurel 6" dia., bears S.21°E., 6½ lks. dist. mkd. ¼ S BT

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - Aug. 18, 1960 - C.S. File 49/47-20

Found - Laurel, dead snag, now 10", S.21°E., 4.0 ft., showing scribing "¼S" in open blaze.
Fir tree, 10", N.64°W., 5.6 ft., uprooted and down. Opened and found scribing.
Corner stone not found.

Set Iron pipe with brass cap mkd; County Surveyors Office
T 30 S R 3 W
¼ S 2 | S 1
1960

Blaze and scribe new bearing trees:
8" Fir S.23°W., 22.0 ft. mkd. ¼ S2 CS BT.
10" Fir S.59°E., 32.8 ft. mkd. ¼ S1 CS BT.
Corner lies on very steep North slope about 1 chain South of small creek.