

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs 25 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. M Bushey Deputy Surveyor under Contract #620, dated June 17, 1893 - (DCSO records Vol. 16 Page 6922)

Set a stone, 14x9x8", 10" in the ground, for 1/4 sec. cor. marked 1/4 on N face, from which

A Fir, 32" dia., bears S.13°E., 13 lks., mkd: 1/4 S BT.

A Fir, 5" dia., bears N.63 1/4°E., 19 lks., mkd: 1/4 S BT.

Ron Quimby - 6/2020 - C.S. File 65/106-35

Found - Orig. 32" now 50", 8' tall Fir stump, 5 X's above bark scribe 1/4 @ chest high (**see photos with report**) good scar @ base. Old BLM warning sign attached S.13°E., 8.6 ft.

Orig. BT to North down face in dirt, 18" Fir N.65°E. (Rec. 63 1/4°E., 19 lks) 12.5 ft. has old BLM tag.

New - Set from bearing stump. 5/8" I.Rod with 2 1/2" alum cap
ROSEBURG RESOURCES COMPANY

T30S R3W

1/4 S 25

S 36

2020

RLS 1654

18" Fir N.65°E., 12.1 ft scribed 1/4 S25 BT

4" Fir S.38°W., 14.0 ft. scribed X, nail in side

4" Fir N.61°W., 8.7 ft. scribed X, nail in side

Alum post 5.0 ft East.