

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6889)

Set ¼ sec. post, from which
A Fir 36" dia., bears S.35°E., 20 lks. dist.
A Fir 24" dia., bears N.80°E., 62 lks. dist.

Douglas Co. Surveyors Office - R.B. Kimberling; P.L. Earle, crew - June 5, 1978 - C.S. File 60/11-14

Found - A Fir stump 36" now 48", bears S.55°E., (Rec. S.35°E.) 13.2 ft. I chop open healed blaze and find scribing "BT"
A Fir stump 24" now 35", bears N.87½°E., (Rec. N.80°E.), 40.9 ft. with visible scribing "BT" in a chopped open blaze.

Set a 1" x 36" Iron pipe with brass cap set 4" above ground and marked: Douglas County Surveyor

T 30 S R 3 W
1 / S 13
4 S 24
1978

New BTs- 12" D.Fir bears N.11°E., 16.0 ft. I double blaze and scribe "¼ S13 CS BT"
5" W.Fir bears S.22°E., 16.4 ft. I double blaze and scribe "¼ S24 CS BT"

Tony Hostetter - For: Seneca Jones Timber Co. - April 2003 - M141-79

Found - 1978 brass cap & accessories as described by Kimberling in 1978, C.S. File 60/11.

New BT - 24" Fir, scribed "S13 ¼ BT", bears N.75°49'E., 43.3 ft. to spike.