

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6925)

-----  
Set a Hemlock post 4 ft. long, 4" sq., 24" in the ground for 1/4 sec. cor. mkd. 1/4 S. on N. face, from which

A Maple 11" dia., bears N.42 3/4°W., 32 lks. dist. mkd. 1/4 S BT.

A Fir 15" dia., bears S.58 3/4°E., 26 lks. dist. mkd. 1/4 S BT.

-----  
Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Jan. 1963 - C.S. File 52/138-8

-----  
Found - Orig. 15" now 30" Fir S.59°E., 17.2 ft. We open and find good scribing "S".

Orig. NW. BT not found.

Set Brass cap at cor. mkd: County Surveyors Office  
T 30 S R 3 W

1/4 S 12  
S 13  
1963

New BTs- 7" Fir bears S.77°W., 6.8 ft. scribed 1/4 S13 CS BT.

16" Fir bears N.21°W., 22.9 ft. scribed 1/4 S12 CSBT

-----  
Greg Lang - For: Rome Creek Timber III LLC - July 2013 - C.S. File 65/79-12A & D

-----  
Found - Brass cap set in 1963; Found original Fir stump 17.20' to the Southeast and the 1963 Fir snag 6.90' to the Southwest.

New BTs- 6 1/2" D.Fir bears N.86°W., 13.90' scribed "1/4 S12 BT"

9" D.Fir bears N.83 1/2°E., 7.80' scribed "1/4 S12 BT"

7 1/2" D.Fir bears S.22 1/4°W., 13.00' scribed "1/4 S13 BT"

7" D.Fir bears S.37 1/2°E., 14.90' scribed "1/4 S13 BT"

Note - Bearings are to the center of the trees and distances are measured to a spike in the side of the trees.

Corner lies on the northerly side of a small ridge, 150'+/- above a gravel road.