

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 36 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6774) and (duplicate info. on Pg. 6907)

-----  
Set a Fir post 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on W. face, from which  
A Laurel 6" dia., N.28¼°E., 24 lks. dist. mkd. ¼ S BT.  
A Maple 7" dia., bears N.60½°W., 22 lks. dist. mkd. ¼ S BT

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Pgs 6796-97)

-----  
I re-establish the old ¼ sec. cor. in its original position as the ¼ sec. cor. on E. bdy. sec. 36, T30S R3W, as follows  
Set a slate stone 12x8x6 ins. 8" in the ground for ¼ sec. cor., marked ¼ on W. face, from which  
A Fir 36" dia., bears S.73°W., 58 lks. mkd. ¼ S36 BT  
A Maple 6" dia., bears N.57 3/4°W., 22 lks. mkd. ¼ S36 BT.

Douglas Co. Surveyors Office - A. Victor Cangie; Peter Earle, crew - Sept. 8, 1976 - C.S. File 59/24-9

-----  
Found - 7" Maple bears N.60¼°W., 14.5 ft. Tree is dead and shows old opened face. Rotted and no visible scribing.  
6" now 8" Laurel stump bears N.28¼°E., 15.8 ft. No visible scribing.

The intersecting point from the BTs places corner point approx. .10 chs. North of an E-W ravine as per orig. line notes. Also found orig. Fir line tree approx. 4.40 chs. North of cor. point. At the cor. point, we find a 40" windfall making it impossible to occupy. WE SET A WITNESS CORNER.

Set 1" x 30" iron pipe with brass cap stamped:

Douglas Co. Surveyor

Witness Corner

T 30 S

R 3 W | R 2 W

S 36

South 47.3 ft. ↓

1/4 cor.

The witness corner bears due North; 47.3' from ¼ corner  
New BTs- 7" W.Fir bears S.84½°W., 9.8 ft. mkd. "WC ¼ S36 CS BT" in a double blaze.

An 8" D.Fir bears S.40½°E., 11.9 ft. mkd. "WC ¼ RP CS BT" in a double blaze.

continued next page

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 36 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Ron Quimby - Crew: N. Fromdahl & L. Heddens - 6/2020 - C.S.  
File 65/106-29

-----

BTs to reference monument (mon. not fd)

18" W.Fir S.84½°W., 9.8' with tag no scar.

Root hole S.40½°E., 11.9'

Established location of RM

No orig. trees to ¼ cor remains

Set - 5/8"x30" IR with 2½" alum cap 47.3 ft south of RM, mkd:

ROSEBURG RESOURCES COMPANY

T30S

R3W R2W

S 36

¼

2020

LS 1654

New - 5" Fir N.27°E., 14.7 ft scribed E¼ S36 BT

18" Fir N.12°W., 48.7 ft scribed E¼ S36 BT

Set alum posts 5' north and 5' south

Note- Corner is approx. 7' North of E-W ravine.

Orig. Line tree stump North 301.5 ft. (rec. 4.40 ch)

Compass decl. 15½°E.