

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 25; and 30, T30-2

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6752)</p> <p>-----</p> <p>Set ¼ sec. post, from which A Maple 5" dia., bears N.10°E., 30 lks. A Maple 10" dia., bears S.10°W., 18 lks.</p>
<p>GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6772-73) and (duplicate info. on Page 6905)</p> <p>-----</p> <p>After diligent search, I am unable to find the ¼ sec. cor. or either of the witness trees. I therefore Set a quartz stone 14x12x8 ins., 10" in the ground for ¼ sec.cor. marked ¼ on W. face, from which An Alder 10" dia., bears N.34°E., 7 lks. dist. mkd. ¼ S BT A Fir 7" dia., bears N.67¼°W., 90½ lks. dist. mkd. ¼ S BT.</p>
<p>Arthur Boyer, Deputy Co. Surveyor - Wit: Geo. Stone; Mr. Stone Sr. - Jan. 31, 1939 - C.S. File 16/11</p> <p>-----</p> <p>No trees standing corresponding to bearing trees in General Land Office field notes. Set steel auto axle, gear on top, midway and on line between NE. and SE. corners of sec. 25, from which A Fir 54" dia. scribed on bark, bears N.47½°W., 41.0 ft. A 10" Fir bears S.49°E., 29.7 ft. measured on slope. A 54" Fir mkd. ¼ S25 T30S R3W CS BT. No trees standing convenient for a BT in Sec. 30, so marked: A 10" Fir same as 54" Fir. Found a 12"x22"x28" granite rock set in ground as if for a quarter corner but no chiseling was legible, this rock bears from the established corner, S.58°W., 5.6 ft.</p>
<p>George Wenderoth, Deputy Co. Surveyor - Wit: Frank Loso, John H. Howell - March 1948 - C.S. File 39/121</p> <p>-----</p> <p>Found steel auto axle, from which 54" Fir N.47°30'W., 41.0 ft. 10" Fir S.49°W., 29.7 ft., slope measurement. Last named BT recorded wrong by Boyer.</p>
<p>Fd. OK, Dec. 1985 and Feb. 1986 by H. Johnstone - M 100-21</p>
<p>1</p>