

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 24 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6751)

-----  
Set ¼ sec. post, from which  
A Laurel 24" dia., bears S.38°E., 40 lks.  
A Maple 6" dia., bears N.60°W., 50 lks.

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6782) and (duplicate info. on Page 6914)

-----  
I find the ¼ sec. cor. greatly decayed with marks nearly obliterated, 24 lks. West of my line, I find one witness tree. At cor. point, I set a Cedar post 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on W. face, from which  
A Laurel 24" dia., (now 30") bears S.38°E., 40 lks. dist. mkd. ¼ S BT. This is the original witness tree.  
I Mark:  
A Fir 8" dia., bears S.50°W., 18 lks. dist. mkd. ¼ S BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page 6786 and Pgs. 6794-95)

-----  
(Page 6786)  
Fd. ¼ sec. cor. witnessed as described by the surveyor general.  
(Pages 6794-95)  
I re-establish the old ¼ sec. cor. in its original position as the ¼ sec. cor. on E. bdy. sec. 24, T30S R3W, only, as follows:  
No stones available, Set a Cedar post 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. on E. bdy. sec. 24, marked ¼ S24 on W. face, from which  
A Fir 10" dia., bears S.50°W., 18 lks. dist. mkd. ¼ S24 BT  
A Fir 28" dia., bears N.88°W., 36 lks. dist. mkd. ¼ S24 BT

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: Fred Seymour - March 14, 1951 - C.S. File 40/302

-----  
Determined by O.B.T.:  
A Fir stump 39" dia., bears N.88°W., 23.7 ft. dist. I chopped this stump out and found scribe.  
A Laurel snag 36" dia., bears S.38°E., 26.4 ft. dist.  
I remark both O.B.T.s.  
At corner point, Set wood stake, from which  
(Cont. Next Page)

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 24 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

<p>A W.Oak 7" dia., bears South 550.0 ft. mkd. ¼ S BT.</p>
<p>Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Feb. 1963 - C.S. File 52/138-42 ----- Found Orig. BTs as recorded by Markham and 7" W.Oak by Markham. Set Brass cap at cor. mkd: County Surveyors Office E ¼ S24 T30S R3W 1963 New BT - 5" Laurel bears S.43°E., 27.5 ft. scribed ¼ CS BT. No other trees near. Corner is at top of steep North slope.</p>
<p>Tony Hostetter - For: Seneca Jones Timber Co. - April 2003 - M141-79 ----- Found - 1963 brass cap as described by Byron C.S. File 52/138, from which 39" Fir stump, face evident, bears N.88°W., 23.7 ft. New BTs- 12" Pine, scribed "S24 ¼ BT", bears N.25°09'E., 14.4 ft. to spike. 16" Fir, scribed "S24 ¼ BT", bears S.55°44'E., 19.2 ft. to spike. 9" Fir, scribed "S24 ¼ BT", bears S.73°35'W., 11.8 ft. to spike.</p>
<p> </p>