

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 700454

PRIMARY CORNER DESCRIPTION Line tree Secs. 13; & 18 T30-02

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6783)</p> <p>-----</p> <p>A fir, 28" dia., on line marked with 2 notches on N &amp; S sides.</p>
<p>GLO retracement by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6793)</p> <p>-----</p> <p>A fir, 30" dia., marked with 2 notches on N &amp; S sides.</p>
<p>Survey by Ronald Geisler, LS #1988 - For: Champion International Corp. - April/May 1986 - M 100-78</p> <p>-----</p> <p>Set a 12" spike in the center of a 35" fir stump, and the following accessories;</p> <p>5" fir bears S.67°E., 55.7'</p> <p>9" fir bears N.52°E., 39.1'</p> <p>Both scribed: X BT</p> <p>Found a recently bucked long alongside stump, with double hack marks on opposite sides of log.</p>
<p>Ken Hoffine - For: Lone Rock Timber Co. - Nov. 2016 - M172-79</p> <p>-----</p> <p>Found - Orig. line tree stump, could not find any evidence of 12" spike.</p> <p>Set - 5/8"x40" iron rod with orange plastic cap in center of stump.</p> <p>5/8"x40" iron rod on section line with orange plastic cap mkd: LONE ROCK TIMBER PLS 2291 bears N.0°07'12"W., 20.00 ft. Put U-post approx. 1.0 ft. north of reference rod.</p> <p>5/8"x40" iron rod on section line with orange plastic cap mkd: LONE ROCK TIMBER PLS 2291 bears S.0°02'58"E., 20.00 ft. Put U-post approx. 1.0 ft. south of reference rod.</p> <p>Found - Uproot record 9" fir as called for by Geisler.</p>
<p> </p>