

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6834)

-----  
Set a granite stone 20x12x6 ins., 15" in the ground for closing cor. of secs. 7 and 18, marked CC on E. with 2 grooves on N. and 4 grooves on S. face, from which  
A Fir 20" dia., bears N.88°E., 104 lks. dist. mkd. T30S R2W S7 BT.  
A Fir 12" dia., bears S.52°E., 14 lks. dist. mkd. T30S R2W S18 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Jan. 1963 - C.S. File 52/138-41

-----  
Found - Orig. 12" now down, 22" Fir S.52°E., 9.3 ft., shows good scribing.  
Orig. NW. BT, not found.  
Corner stone not found.

Set brass cap at cor. mkd: County Surveyors Office

T 30 S  
R3W |  $\frac{S}{S}$   $\frac{7}{18}$  C.C. R2W  
1963

New BTs- 7" R.Fir S.62°E., 48.0 ft. scribed CC S18 CS BT.  
7" Cedar N.54°E., 84.4 ft. scribed CC S7 CS BT.

BLM survey by Harvey E. Wofford, Cadastral Surveyor, under Group #705, surveyed Sept/Oct. 1970 - (DCSO records Vol. 35 Page(s) 14517-18)

-----  
The true point for closing cor. of secs. 7 and 18, established by the DCSO in 1963, monumented with an iron post 1½" dia., firmly set, projecting 12" above ground, with brass cap mkd. in 1963

from which a tree by the County Surveyor  
A Fir 8" dia., bears S.60¼°E., 69 lks. dist., with healed blaze.

and a new bearing tree  
A Fir 5" dia., bears N.56½°E., 89 lks. dist., mkd. T30S R2W S7 CC BT.

From this point, the original closing cor. of secs. 7 and 18, bears N.89°42'W., 4 lks. dist., monumented with an iron rod, ½" dia., firmly set, projecting 6" above the ground, from which the remaining original bearing tree:

(Cont. Next Page)

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 700501

PRIMARY CORNER DESCRIPTION C C for Secs. 7 & 18 only, T30-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A root hole bears S.52°E., 14 lks. dist. with a down Fir alongside, 16" dia., with fragmentary scribe marks visible on open blaze.  
(Could find no source for found iron rod) V. Laugen, 8/96

From this same point, the cor. of secs. 12 and 13 only, T30S R3W, bears S.0°22'E., 71 lks. dist.

Greg Lang - For: Rome Creek Timber III LLC - July 2013 - C.S. File 65/79-12A  
-----  
Found 1970 BLM B. Cap, set as the closing corner for Secs. 7/18 bears N.89°26'07"E., 0.20' from line.

Ken Hoffine - For: Lone Rock Timber Co. -Nov. 2016 - M172-79  
-----  
Found - 1963 BCIP closing corner.  
¾" iron rod bears N.89°45'29"W., 2.46 ft. (rec. from map M100-78 is N.89°42'W., 2.64')  
20" D.Fir bears S.60¼°E., 45.4 ft. (rec. S.60¼°E., 45.54 ft.) healed face and tag.  
19" D.Fir bears N.56°E., 58.6 ft. (rec. N.56½°E., 58.74 ft.) healed face and tag.  
Note - Corner is approx. 1.0 ft. above ground level and is approx. 60 ft. north of draw.  
Metal U-post approx. 0.5 ft. north of corner.