

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6785) and (duplicate info. on Page 6917)

Set a Cedar post 4 ft. long, 4" sq., 24" in the ground for 1/4 sec. cor. marked 1/4 S on W. face, from which
A Fir 36" dia., bears S.61°W., 147 lks. dist. mkd. 1/4 S BT.
A Fir 11" dia., bears N.2 1/2°E., 76 lks. dist. mkd. 1/4 S BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6787 and 6792)

(Page 6787)
Found 1/4 sec. cor. which is a Cedar post 4" sq., 12" above ground, marked and witnessed as described by the surveyor general.

(Page 6792)
(40.08 1/2 chs.)
Point midway on W. bdy. sec. 7. However, as this point is within limits of 25 lks. with the old 1/4 sec. cor., I therefore re-established the former 1/4 sec. cor. as the 1/4 sec. cor. common to secs. 7 and 12.
(40.25 chs. South)
Set a Cedar post 3 ft. long, 4" sq., 24" in the ground for 1/4 sec. cor. mkd. 1/4 S12 on W. and 7 on E. face, from which
A Fir 12" dia., bears N.2 1/2°E., 76 lks. dist. mkd. 1/4 S7 BT.
A Fir 36" dia., bears S.61°W., 147 lks. dist. mkd. 1/4 S12 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Jan. 1963 - C.S. File 52/138-40

Found - Orig. 11" now 30" Fir, N.2 1/2°E., 50.2 ft., shows good scribing, previously opened.
Orig. SW. BT, shows good scar. Checks record.
Set Brass cap at cor. mkd: County Surveyors Office
T 30 S
1/4 R3W S12 | S 7 R2W
1963
New BTs- 16" R.Fir bears S.46 1/2°E., 28.4 ft. scribed 1/4 S7 CS BT.
20" R.Fir bears N.28°W., 18.5 ft. scribed 1/4 S12 CS BT.

(Cont. Next Page)

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 12; & S. 7, T30-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM survey by Harvey E. Wofford, Cadastral Surveyor, under Group #705, surveyed Sept/Oct. 1970 - (DCSO records Vol. 35 Page(s) 14512-13)

The ¼ sec. cor., perpetuated and recorded by DCSO in 1963, monumented with an iron pipe 1¼" dia., firmly set, projecting 12" above ground with brass cap mkd. in 1963 from which the remaining original bearing tree
A Fir 40" dia., bears N.2½°E., 76 lks., with fragmentary scribe marks visible on opened blaze.
and a tree of which I have no record
A Fir 24" dia., bears N.29½°W., 28 lks. with healed blaze.

Greg Lang - For: Rome Creek Timber III LLC - July 2013 - C.S. File 65/79-12A & F

Found - 1963 Brass cap set by County Surveyor.
A 34" D.Fir bears N.26½°W., 18.5'
A 24" D.Fir bears S.48°E., 28.4'
A 48" D.Fir bears N.2¼°E., 49.0' (record is 50.2')
New BTs- 15" D.Fir bears S.62¼°W., 33.40' scribed "¼ S12 BT"
Note - Bearings are to the center of the trees and distances are measured to a spike in the side of the trees.
Corner lies on a Northeast slope about 75' below existing logging rd. Also 80' North of ridge top.