

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 1 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6918)

Set a Fir post 4 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor. marked ¼ S on W. face, from which

A Fir 28" dia., bears N.57½°W., 37½ lks. dist. mkd. ¼ S BT

A Fir 26" dia., bears N.89°E., 52¼ lks. dist. mkd. ¼ S BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6788 and Pg. 6790)

(Page 6788)

The ¼ sec. cor. which is a Fir post 4" sq., 12" above ground, marked and witnessed as described by the surveyor general.

(Page 6790)

In its original position, I re-establish the old ¼ sec. cor. as the ¼ sec. cor. on E. bdy. of Sec. 1, T30S R3W, only as follows:

The old post is badly decayed, no stones available, Set a Madrone post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. on E. bdy. Sec. 1, T30S R3W, marked ¼ S1 on W. face, from which

A Madrone 24" dia., bears S.41°W., 10 lks. dist. mkd. ¼ S1 BT.

A Fir 36" dia., bears N.57½°W., 38 lks. dist. mkd. ¼ S1 BT.

Obliterate marks on former bearing tree referring to Section 6.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Dec. 1962 - C.S. File 52/126-88

Found both original BTs. Orig. SW. BT, shows good scribing. New BT - 7" R.Fir bears S.51°W., 15.0 ft. scribed ¼ S1 CS BT.

BLM resurvey by Peter Peterson and Daniel Berry under Group #749, surveyed July/Aug. 1971 (DCSO records Vol. 36 Page(s) 14915)

The ¼ sec. cor. of sec. 1 only, determined at record bearing and distance from the original bearing trees:

A Fir 30" dia., bears S.86°E., 52¼ lks. dist., with healed blaze. (Rec. bearing N.89°E.) Mensch reported destroying marks on this tree in 1908.

(Cont. Next Page)

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 700640

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 1 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir 40" dia., bears N.57½°W., 38 lks. dist., with healed blaze. (Mensch record)

and a bearing tree marked by Mensch in 1908

A Madrone 32" dia., bears S.41°W., 10 lks. dist. with no marks remaining on opened and rotted blaze.

and a bearing tree mkd. by the County in 1962:

A Fir 10" dia., bears S.44½°W., 24½ lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

1/4
S 1
T 30 S
R 3 W
1971

Fd. OK, Nov. 1984 by H. Johnstone - M 97-65