

PRIMARY CORNER DESCRIPTION NE Cor. Sec. 1 (NE Tsp Cor.)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6919)

At point of intersection, I set a Fir post 4 ft. long, 4" sq., 24" in the ground for closing cor. to T30S Rs. 2 and 3 W. marked CC T30S on S.; R2W S6 on E.; and R3W S1 on W. faces with 6 notches on S. E. and W. faces, from which
A Fir 17" dia., bears S.43½°E., 53 lks. dist. mkd. T30S R2W S6 BT.
A Fir 10" dia., bears S.68°W., 35½ lks. dist. mkd. T30S R3W S1 BT.
A Fir 11" dia., bears N.15 3/4°E., 17 3/4 lks. dist. mkd. CC T30S Rs. 2 and 3 W. BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6788 and Pg. 6790)

(Page 6788)
The old closing cor. to Tp. 30 S. R's 2 and 3 W., which is a decayed Fir post marked and witnessed as is described by the surveyor general.
(Page 6790)
The old closing cor. of Tp 30 S, R 2 and 3 W., I re-establish this cor. in its original position as the NE. cor. of T30S R3W only, as follows:
The old post is badly decayed. Set a sandstone 18x8x4 ins., 12" in the ground for NE. cor. of T30S R3W, marked with 6 notches on S. and W. edges, from which
A Fir 10" dia., bears S.68°W., 36 lks. dist. mkd. T30S R3W S1 BT.
Obliterate marks on former brg. tree referring to T30S R2W.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Dec. 1962 - C.S. File 52/126-89

Found - Orig. 10", now down, 14" Fir S.68°W., 23.8 ft., shows scribing.
No other original BTs found.
Do find shattered stone at corner.
Set Brass cap at corner mkd. County Surveyors Office, 1962.
New BTs- 9" Fir bears S.77°W., 13.9 ft. scribed S1 T30S R3W CS BT.
10" Hemlock bears N.78°E., 33.6 ft. scribed S6 T30S R2W CS BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION NE Cor. Sec. 1 (NE Tsp cor)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM resurvey by Peter Peterson and Daniel Berry under Group #749, surveyed July/Aug. 1971 - (DCSO records Vol. 36 Page(s) 14915-16)

The NE. cor. of T30S R3W, perpetuated and recorded by Byron in 1962, monumented with an iron post, 1½" dia., firmly set, protruding 14" above ground with properly mkd. 1962 brass cap, from which the original bearing trees:

A Fir 18" dia., bears N.15 3/4°E., 17 3/4 lks. dist., with healed blaze. (Bushey record)

A root hole bears S.43½°E., 53 lks. dist., with a down Fir, 22" dia., alongside, with no marks remaining. (Bushey record)

A root hole bears S.68°W., 36 lks. dist., with a down Fir 16" dia., alongside, with scribe marks T30S R3W visible on opened blaze. (Mensch record)

and bearing trees mkd. by Byron:

A Hemlock 12" dia., bears N.77°E., 51 lks. dist., with scribe marks S RW S6 CS visible on open double blaze.

A Hemlock 10" dia., bears S.79°W., 21 lks. dist., with healed blaze.

and a new bearing tree:

A Fir 8" dia., bears S.39°W., 27 lks. dist. mkd. T30S R3W S1 BT.

Corner falls at bottom of descent, slopes E.

Fd. OK, Nov. 1984 by H. Johnstone - M 97-65