

Douglas County Surveyor's Record of
Government Corners Renewed

T 30 T. S. R 4 E R/W/W.M.

KOKE-CHAPMAN CO. EUGENE, ORE. 21881

B. Malotte
J. Swanson
R. Frost
Jackson County Surveyors Office
August, 1978
C.S. 58/183

1/4 Corner for Sec. 6; and Sec. 1 of T.30-3 E.
Found - Projecting 4 ins., the orig. 1 in. iron pipe with standard
GLO brass cap properly marked as recorded by H. Raymond in 1927.
Orig. BT, a sawed fir stump, 18" bears record S.75°E., 26.40 ft.
to center.
Orig. White pine, 37" with healed single blaze, bears N.15°W.,
12.8 ft. to center. (Rec. N.15°W., 13.20 ft.)
I re-mark this tree CS BT.
New BT - 9" White fir bears S. 55 3/4°E., 16.1 ft. to center of tree at
lower blaze.
Corner lies 66 ft. north of ridge top C. SE.

8/11/78

1/4 Corner for Sec. 4; and Sec. 33 of T.29-4E.
Found - Projecting 9 ins., the 1 in. iron pipe with a properly
marked 1929 GLO brass cap.
Orig. BT, recorded by H. Raymond in 1929, 22" Hemlock with
healed single blaze, bears S.75 1/2°E., 47.85 ft. to center.
(Rec. S. 75 1/2° E., 48.18 ft.)
15" Fir snag with healed single blaze, bears N.71 1/2°W.,
37.93 ft. to center. (Rec. N.70°W., 38.28 ft.)
New BT - 14" White pine, bears N.64 1/2°W., 9.62 ft to center of tree
at lower blaze.
Corner lies about 300 ft. west of location marker on 8 ins. diam. white
pine located approx. 50 ft. west of road.

8/9/78

Section corner common to secs. 1 and 2; and secs. 35 & 36 of T.29-4E.
Found - Projecting 8 ins. in mound of stone, the orig. 2 ins. diam.
iron pipe with 1929 GLO brass cap properly marked as recorded
by H. Raymond in 1929.
Orig. BT, a stump of a down 9 ins. Fir, scribed as recorded, bears
N.34°E., 48.6 ft. to center. (Rec. N.34°E., 48.84 ft.)
18" White Pine with scribe mkd. visible inpartly healed blaze,
bears S.48 1/2°E., 33.25 ft. to center. (Rec. S.48 1/2°E.,
33.0 ft.)
The stump and base of a down lodge pole pine 9 ins. scribed as
recorded, bears S.2°W., 23.0 ft. to center. (Rec. S.2°W., 23.76)
Fir snag, 12", with healed single blaze bears N.38 1/2°W., 23.10
ft. to center. (Rec. N.38 1/2°W., 22.44 ft.)
New BT's- I mark the following trees CS BT and take measurements to center
of trees at lower blaze:
5" Lodge pole pine bears N.40 1/2°E., 18.0 ft.
10" White pine bears S.6°W., 23.25 ft.
15" Lodge pole pine bears N.52°W., 40.80 ft.

8/5/78

Section corner for Secs. 3 and 2; and Secs. 34 and 35 of T.29-4E.
Found - Bent over, the orig. 2 x 36 in. iron pipe with attached 1929
GLO brass cap properly marked as recorded by H. Raymond.
I remove, straighten and replace the above, in the orig. position, 26 ins.
in the ground from which:
24" D. Fir with healed blazes bears S.27°E., 25.64 ft. to center
(Rec. S.27°E., 25.74 ft.)
17" D. Fir with healed single blaze, bears S.56°W., 46.32 ft. to
center. (Rec. S.56°W., 46.86 ft.)
Pine snag, 22 ins. containing scribe marks including "4" and
"34 BT" in partly exposed face, bears N.57°W., 37.88 ft. to
center. (Rec. N.57°W., 38.28 ft.)
NE BTnow gone.
I mound stones around corner, mark the following trees CS BT and take
measurements to center of trees at lower blaze:
White fir, 13 ins. bears N.42°E., 147.1 ft.
Shasta red fir, 25 ins. bears N.83°W., 43.0 ft. to center.
Comer lies approx. 85 ft. S.6°E., from location marker on 25" diam. Fir,
alongside road.

8/7/78