Douglas County Surveyor's Record of Government Corners Renewed

T 30 T. S. R 4 E E R. W/W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

5

1/4 Corner common to section 2 and Sec. 35 of T29-4E.
Found - 2 ins. deep, the 1 in. diam. iron pipe with standard GLO brass cap properly marked as recorded by H. Raymond in 1929.
Orig. BT, Shasta red fir, 25ins. with healed single blaze bears N.18°E 34.66 ft. to center. (Rec. N.18°E., 34.98 ft.)
The NW branch, 20 ins. diam. of a double fir, sawed stumps bears S.83°E., 34.5 ft. to center. (Rec. S.83°E., 34.32 ft.)
I mound stones around corner and mark a new tree CS BT:
Shasta red fir, 24 ins. diam., bears S.29°W., 36.64 ft. to center of tree at lower blaze.
Corner lies about 225 ft. south of lo-ation marker on 10 in. diam. Fir (mkd. with axed "X") alongside road.

— — — — — 8/7/78

6

1/4 Corner common to Sec. 3; and Sec. 34 of T.29-4E.
Found - projecting 3 ins., the 1 in iron pipe with 1929 GLO brass cap properly marked as recorded by H. Raymond in 1929.
Orig. BT, Pine snag, 14 ins. containing scribe mkd. in partially exposed face, bears N.35°E., 21.25 ft. to center. (Rec. N.35°E 21.12 ft.)
White fir, 16" with healed blazes, bears S.58°E., 14.84 ft. to center. (Rec. S.58°E., 15.18 ft.)
I mark new trees CS BT and take measurements to center of trees at lower blaze: 14" Hemlock, bears N.88°E., 28.48 ft.
22" White fir, bears S.86°W., 18.29 ft.

— — — — — 8/7/78

7

Township corner common to Sec. 1; and Sec. 6 of T.30-5E; section 36 of T.29- 4E; section 31 of T.29-5E.
Found - projecting 8 ins. the 3 in iron pipe with standard GLO B.C. bra cap properly marked as recorded by H. N. Raymond in 1929.
Orig. BT, sawed Fir stump shell, 36 ins. bears record N.32 N.32°E , 54.78 ft. to center.
Fir snag, 26 ins. containing scribe mkd including"5E S6 BT" in partly exposed single face, bears S.80 1/2°E., 85.92 ft. to center. (Rec. S.80 1/2°E., 85.14 ft.)
White Fir, 38 ins. with healed single blaze, bears S.81°W., 26.9' to center. (Rec. S.81°W., 28.38 ft.)
Shasta red fir, 41 ins. with healed single blaze, bears N.36°W., 25.9 ft. to center. (Rec. N.36°W., 27.06 ft.)
I mark new trees CS BT and take measurements to center of trees at lower blaze: White fir, 22 ins. bears N.16°E., 32.0 ft.
White fir, 10 ins. diam., bears S.83°E., 64.78 ft.
Corner lies at north edge of marshy stream bed, 25 ft. south of south edge of clear cut and about 400 ft. west of location marker on 16 ins. Fir alongside road. C N-S.

— — — — — 8/3/78

8

1/4 Corner for Section 1; and sec. 36 of T.29-4E.
Found - the orig. 1 x 36 ins. iron pipe with standard GLO brass cap properly marked 1929, lying horizontal 6 ins. below th surface of the ground.
I straightened and re-set the above, 26 ins. in the ground in its orig. position.
Orig. BT recorded by H. Raymond in 1929 found as follows:
14" White fir with healed single blaze, bears record S.8°W. 27.06 ft. to center.
Shasta red fir, 38 ins. diam. with healed single blaze, bea. record, N.23°W., 32.34 ft. to center.
Corner lies in cat logged area, about 300 ft. east of location marker on 12 ins. Fir, alongside road.

— — — — — 8/3/78

9

Section corner common t- sections 4 and 3; and Secs. 33 and 34 of T.29-4E.
Found - Original bearing trees recorded by H. Raymond in 1929:
Fir snag, 14 ins. with healed single blaze, bears record N.34°E. 9.90 ft. to center.
SE BT now gone.
- Shasta red fir, 24 ins. containing scribe mkd in partially exposed single face, bears S.56°W., 16.11 ft. to center. (Rec. S.56°W. 16.50 ft.)

— CONT NEXT PAGE

B. Malotte
J. Wvanson
R. Frost
Jackson County Surveyors Office
August. 1978
C.S. 58/183