Douglas County Surveyor's Record of Government Corners Renewed

T 30 T. S. R 4 E R/W/W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21661

9

C O N T.

Found, Douglas Fir, 23 ins. diam., with healed single blaze, bears N.19 1/2°W., 17.77 ft. to center. (Rec. N.19 1/2°W. 17.16 ft.)

Original monument not found.

From the following evidence, at the location described, I set a 1" x 36" G.I pipe with a 2 1/2" bronze disc mkd: Jackson County 1978 T29S R4E 33 34 4 3 T30S. I mound stones around corner and mark a new tree CS-B' 6" Hemlock bears S.21°W., 25.43 ft. to center of tree at lower blaze.

Note: No trees available in NE quadrant. Corner lies about 40 ft. South of road, C E-W.

B. Malotte
R. Frost
Jackson County Surveyors Office
August, 1978
C.S. 58/183

8/7/78

10

Section corner common to Secs. 6 and 7; and sections 1 and 12 of T.30-3E

Found - Flush with the ground, the original 2 ins. iron pipe with standard GLO brass cap properly marked as recorded by H. Raymond in 1927.

The single remaining bearing tree, now a sawed fir stump, scribed "1 BT" in opened remaining portion of face, bears record, N.46 1/2°W., 43.56 ft. to center.

I mark new trees CS Ce and take measurements to center of trees at lower blaze:
27" Douglas fir, bears N.19°E., 62.7 ft.
17" Hemlock bears S.67°E., 88.2 ft.
39" D. Fir bears S.81°W., 54.5 ft.
24" W. Fir bears N.20°W., 6.0 ft.

Corner lies approx. 115 ft. West of trail along top of river (right) bank.

L-77

8/14/78