

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 039050

PRIMARY CORNER DESCRIPTION Pt. on SE Bdy Beckworth DLC #39

Alias <u>041020</u>	Description <u>NW Cor. John Boyle DLC #41</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - GLO survey by Bowman and Burnett, under Contract dated Sept. 1855 (DLC survey) (Pg. 597 and 602 DLC Volume)

(Page 597)

Set post on right bank of river 100 lks. N. of true cor. marked, from which

A B.Oak 15" dia., bears S.80°W., 22 lks. dist.

(Page 602)

Set a post 100 lks. N. of true corner, from which

A B.Oak 30" dia., bears S.65°E., 31 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (Page 699 DLC Volume)

At 1.00 chn. North of true cor., I Set a basalt rock 12 x 8 x 6 ins., 8" in the ground, for witness corner to NW. Cor. of Claim, marked C. 41 W.C. on SE. face, from which

A B.Oak 36" dia., bears S.65°E., 31 lks. dist. mkd. T30S R4W C. 41 WC. BT. This is the old bearing tree which I remark.

F.C. Frear, Douglas Co. Surveyors office - Wit: Ralph Knight and Opher Perdue - Nov. 11, 1919 - Field Book 47 Pg. 40

Set on right bank of South Umpqua River 100 lks. North of true corner. I reestablish same from old BTs and remark same. Also Set in a 1½" x 36" iron pipe, from which

A 48" B.Oak bears S.82°W., 19 lks. old BT, remarked.

A 48" B.Oak bears S.63°E., 30½ lks., old BT, remarked.