

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 039090

PRIMARY CORNER DESCRIPTION Pt. on SE Bdy Beckworth DLC #39

Alias 042020 Description Ext. L Cor. Kemuel DLC #42  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - GLO survey by Bowman and Burnett, under Contract dated Sept. 1855 (DLC survey) (Pg. 598 and 603 DLC Volume)  
-----  
(Page 598)  
Corner in right edge of river - impracticable to erect a permanent cor.  
(Page 603)  
Corner in right edge of S. Umpqua, Raised mound 50 lks. South with trench

Resurvey - Wm. Thiel, under Contract dated Feb. 5, 1889 (DLC Volume, page 695 & 701)  
-----  
Cor. is in the river; set as witness corner 108 lks. South & 68 lks. E of true cor. a basalt stone marked 39 WC on NW face, (page 701, 42 WC on SE face) 9x8x7" 6" in the ground, raised a mound of stone alongside.

Briggs - Sept. 30, 1900 - Vol. 2 page 103  
-----  
Post. Marked new BT:  
Maple 16" S.62°E., 35 lks.

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, and Robert Browning, Surveying Technician, under Group #1686, surveyed May 1993 thru April. 1995 - (DCSO records Vol. 52 Page(s) 20136)  
-----  
Point for the exterior L cor. of DLC 42, at proportionate dist., determined by the Grant Boundary Method between the reestablished SW. cor. of DLC 42 and the reestablished NE. cor. of DLC 42, there is no remaining evidence of the original corner.  
Set a stainless steel post, 28" long, 2½" diam., 46" in the ground, with brass cap mkd.  
T30S R4W  
S 8  
-----  
C 42  
1994  
from which  
A cottonwood, 20" diam., bears S.66 3/4°E., 83 lks., mkd. C42 BT.  
A maple, 22" diam., bears S.8½°W., 77 lks., mkd. X BT.  
Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.  
The corner is located at the S. edge of a hay field.