

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 042060

PRIMARY CORNER DESCRIPTION SE Cor. Charles Kemuels DLC #42

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - GLO survey by Bowman and Burnett, under Contract dated Sept. 1855 (DLC survey) (Page 604 DLC Vol.)

-----  
Set a post marked, from which  
A Maple 6" dia., bears N.20°W., 12 lks.

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, and Robert Browning, Surveying Technician, under Group #1686, surveyed May 1993 thru April. 1995 - (DCSO records Vol. 52 Page(s) 20126)

-----  
Point for the SE. cor. of DLC 42, at proportionate dist., determined by the Grant Boundary Method between the original SE. cor. of DLC 41 and the original SW. cor. of DLC 44, there is no remaining evidence of the original corner.

Set a stainless steel post, 28" long, 2½" diam., 24" in the ground, with brass cap mkd. T30S R4W

C 42

S 17

1994

from which

A fir, 6" diam., bears S.42°E., 63 lks., mkd. S17 BT.

A fir, 12" diam., bears N.20 3/4°W., 83 lks., mkd. C42 BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

The corner is located N. 25° E., 0.30 chs. of a fence corner, with woven wire fence extending N. and barbed wire fence extending W.