

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 043030

PRIMARY CORNER DESCRIPTION SW Cor. Andrew Chapman DLC #43

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - GLO survey by Bowman and Burnett, under Contract dated Sept. 1855 (DLC survey) (Page 606 DLC Vol.)

Set a post marked, from which
A B.Oak, 24" dia., bears N.13°E., 20 lks.

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, and Robert Browning, Surveying Technician, under Group #1686, surveyed May 1993 thru April. 1995 - (DCSO records Vol. 52 Page(s) 20127)

Point for the SW. cor. of DLC 43, on the E. bdy. of DLC 42, at proportionate dist., determined by the Grant Boundary Method between the original SE. cor. of DLC 41 and the original SW. cor. of DLC 44, there is no remaining evidence of the original corner.

Set a stainless steel post, 28" long, 2½" diam., 25" in the ground, with brass cap mkd.

T30S R4W
C 43
C 42 _____
S 17
1994

from which

A fir, 9" diam., bears N.47½°E., 40½ lks., mkd C43 BT.

A fir, 16" diam., bears S.17°E., 54 lks., mkd. S17 BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

The corner is located N. 15° E., 0.38 chs. dist. of a fence corner, with woven wire fences extending N., S., and E.