

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 044010

PRIMARY CORNER DESCRIPTION NE Cor. Joel Thorn DLC #44

Alias <u>046060</u>	Description <u>SE Cor. Alexander Dumond DLC #46</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - GLO survey by Bowman and Burnett, under Contract dated Sept. 1855 (DLC survey) DLC Volume Page 608

(Page 608, DLC 44)

Set a post marked a quadrangle trench and stone in the center.

(Page 609, DLC 46)

Set a post in prairie raised mound with trench as per instructions.

W.F. Briggs - For: Dumonds - Oct. 19, 1887 - Field Book 3
Pg. 7

Set post, marked new BT:
B.Oak 16" S.2°W., 949 lks.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records DLC Vol. Page 707 and 709)

(Page 707, DLC 44)

As the post set for this corner is gone, and cultivation has obliterated any marks on the ground, I went to the NE Cor. of Claim No. 46 and run South to the SE. corner of Claim No. 44. I found the distance to be 75.23 chns. insted of 77.57 chns. Therefore Cl. 44 will lose its proportion of difference (234 lks.) namely 61 lks. At the point 1939 lks. N. from SE. Cor., I restore this corner by setting a basalt stone 18 x 10 x 8 ins. marked 44 on SW. face, 12" in the ground, and raised a mound of stone alongside.

(Page 709, DLC 46)

The SE Cor.; also the NE. cor. of Claim No. 44; set a basalt stone 18x10x8 ins. in dia., 12" in the ground, marked 46 on NW. face, and raised a mound of stone alongside. (Note, as the post set for this cor. is gone, and cultivation has obliterated all marks upon the ground, I continued this line to the SE. corner of Claim No. 44 I found the distance to be 75.23 chns. instead of 77.57 chs.; therefore Claim No. 46 will lose it proportions of difference (234 lks.) namely 173 lks.